



NEW ENGLAND ROPES

est. 1967

YACHTING ROPES

2025/2026

How to choose THE RIGHT PRODUCT

What do you need this line for?

MOORING & ANCHORING

OR

RUNNING RIGGING?

MOORING AND ANCHOR LINES*


Your boat m	Weight t	Ø Mooring line mm	Ø Anchor line mm
6-8	2	8-10	12
9	4	12	14
10	5	12	16
11	7	14	16
12	8	14	18
14	11	16	20
16	12	18	20
18	20	24	24
24	22	26	26

HALYARDS AND SHEETS*


Your boat m	Ø mm Halyards Spi	Genoa	Main	Ø mm Sheets Spi	Genoa	Main
6-8	8	8	8	10	10	10
9	8	10	10	10	12	10
10	10	10	10	10	14	12
11	10	12	10	12	14	12
12	12	12	12	12	14	12
14	12	12	12	14	14	12
16	12	14	12	14	14	14
18	14	14	14	14	14	14
26	16	16	16	16	16	16

*When using lines made of Dyneema®, the diameter can be reduced by 2 mm! The specified values are experience-based values of New England Ropes®. They are average values which, however, can vary from one yacht type to another.


The four basic types of rope construction



double-braid



single-braid



three-strand



8-plait

PREDEFINE

1. size of Clutches/Jammers
2. size of Blocks
3. size of Selftailing head on winch



DEFINE

maximum
working
load



USE

rope that uses only (max.)
20% of available
tensile strength



WARNING

The misuse of ropes can be dangerous. Our products may only be used for the purpose they are designed for. Do not use them for personal protection or lifting purposes as specified in EU Directive 2006/42/EC, unless the products are clearly identified as suitable for such purposes under relevant standards. The user is responsible for the proper application and supervision of the rope's use and assumes the user is familiar with the necessary safety precautions. We recommend a splice as end connection for all of our products. For Dyneema® products (such as HTS-99 for example) a splice is the only option that should be used, as knots can come undone under a load.


ELONGATION

The following diagram shows the elongation versus the applied load for a number of fiber properties used to produce New England Ropes®. The recommended working load at max. is 20% of the breaking load. The red line in the graph signifies this level.

Example: At the recommended working load of max 20%, Polyester fibers elongate by little under 3%, whereas PBO fibers and SK99 fibers not even reach elongation values of 1%.

Beware: when using a rope for its first time, elongation may be much higher than in the graph!

Breaking Load vs Elongation at Break Fiber Properties



	Elongation %	cm
GP	below 0.3	<6
High Tech	0.31	20
Cruising	2-3	40-60

LINE SELECTION GUIDE

NEW ENGLAND ROPES® makes line selection easy:

- ① **CHOOSE YOUR APPLICATION** e.g. (Main Halyard)
- ② **CHOOSE TYPE OF SAILING** e.g. (Cruiser)
- ③ **SELECT YOUR BOAT SIZE** e.g. (35 ft.)
- ④ **MATCH COLOR CODE IN RECOMMENDED CELL TO PRODUCT TYPE ON RIGHT.** This will give you the best selection and diameter of line for given application.

TO UPGRADE IN ANY CASE, modify your selection in type of sailing category. In most cases, choosing a better performing line will substantially lower the stretch and in most cases allow you to reduce diameter by 10-15%. The net result will be a line, which will have low stretch, is lightweight and will control sail shape more precisely.

REPLACE YOUR WIRE HALYARDS WITH ALL ROPE HALYARDS

Rope halyards are easier to handle and significantly lighter than wire halyards. Endura Braid® or VPC is an ideal replacement for wire halyards on cruising yachts. For race boats and large cruising yachts, use V-100 or T-900.

WIRE HALYARD REPLACEMENT GUIDE

7 x 19 Wire Size	1/8"	5/32"	3/16"	7/32"	1/4"
Endura Braid® & VPC Replacement Size	5/16"	3/8"	7/16"	1/2"	9/16"
V-100 and T-900 Replacement Size	6mm	6mm	8mm	10mm	12mm

Line selection guide

Line selection guide			3. BOAT SIZE																										
			in feet	15			20			25			30			35			40			45			50				
1. YOUR APPLICATION	MAIN SHEET	2. TYPE OF SAILING	Cruising	8mm						10mm						11mm						12mm							
			Club Racing	8mm						10mm						10mm						11mm							
			Grand Prix Racing	6mm						8mm						10mm						11mm							
			One-Design/Sport Boat	6mm						7mm						8mm													
	JIB SHEET	Cruising	6mm			8mm						10mm						11mm						12mm					
		Club Racing	6mm			8mm						10mm						12mm											
		Grand Prix Racing	6mm			8mm						10mm						11mm						12mm					
		One-Design/Sport Boat	6mm						7mm						8mm														
	SPIN SHEET	Cruising	6mm						8mm						10mm			10mm			11mm								
		Club Racing	6mm									8mm						10mm						10mm			8mm		
		Grand Prix Racing	6mm						8mm						10mm						10mm			11mm					
		One-Design/Sport Boat	6mm						7mm						8mm														
	LIGHT AIR SPIN SHEET	Cruising	6mm						6mm						8mm			10mm											
		Club Racing	6mm						6mm						8mm			10mm											
		Grand Prix Racing	6mm						8mm						10mm														
		One-Design/Sport Boat	7mm									9.5mm																	
	TRAVELLER	Cruising	6mm						8mm						10mm														
		Club Racing	6mm						8mm						10mm														
		Grand Prix Racing	6mm						8mm						10mm														
		One-Design/Sport Boat	6mm						7mm						8mm						10mm								
	TACK LINE	Cruising							8mm									8mm			10mm			11mm			12mm		
		Club Racing	6mm						7mm						8mm			10mm			11mm			12mm					
		Grand Prix Racing	6mm						7mm						8mm			10mm			11mm			12mm					
		One-Design/Sport Boat	6mm						7mm						8mm			10mm											
	MAIN HALYARD	Cruising	6mm						8mm						10mm						11mm			12mm					
		Club Racing	6mm									8mm						10mm						11mm					
		Grand Prix Racing	6mm									8mm						10mm						11mm					
		One-Design/Sport Boat	4mm			5mm						6mm						8mm			10mm								
	JIB HALYARD	Cruising	6mm						8mm						10mm						11mm			12mm					
		Club Racing					6mm						8mm						10mm			11mm							
		Grand Prix Racing	6mm									8mm						10mm			11mm								
		One-Design/Sport Boat	4mm			5mm						6mm						7mm			8mm						10mm		
SPIN HALYARD	Cruising	6mm						8mm						10mm						11mm			12mm						
	Club Racing					6mm						8mm						10mm			11mm								
	Grand Prix Racing	6mm									8mm						10mm			11mm									
	One-Design/Sport Boat	4mm			4mm						5mm			8mm						10mm						10mm			
SPINNAKER TOPPING LIFT	Cruising	5mm						6mm						10mm						11mm									
	Club Racing	5mm						6mm			8mm			8mm			10mm												
	Grand Prix Racing	6mm									8mm						10mm			11mm									
	One-Design/Sport Boat	4mm			5mm						6mm						8mm												
FORE GUY	Cruising	5mm						6mm						10mm						11mm									
	Club Racing	5mm						6mm						8mm			8mm						10mm						
	Grand Prix Racing	5mm						6mm						8mm						10mm									
	One-Design/Sport Boat	4mm		5mm		6mm						8mm						10mm											
			boat size in feet	15			20			25			30			35			40			45			50				

Color codes

Sta-Set®	Poly-Tech	Viper-24	Regatta Braid	Flight Line	Endura Braid®	T-900	V-100	VPC	Spiderline	SK-78 / SK-99
----------	-----------	----------	---------------	-------------	---------------	-------	-------	-----	------------	---------------

LINE RECOMMENDATIONS

1. BOOM LIFT

- ✓ STA-SET®
- ✓ HSR-75
- ✓ VIPER-24

2. MAIN HALYARD

- ✓ STA-SET®
- ✓ VPC
- ✓ ENDURA BRAID®

3. JIB/SPINNAKER HALYARD

- ✓ STA-SET®
- ✓ VPC
- ✓ ENDURA BRAID®

4. TOPPING LIFT

- ✓ STA-SET
- ✓ VPC
- ✓ ENDURA BRAID

5. MAIN SHEET

- ✓ STA-SET®
- ✓ VIPER-24
- ✓ ENDURA BRAID®

6. JIB SHEETS

- ✓ STA-SET®
- ✓ ENDURA BRAID®
- ✓ POLY-TEC

7. SPINNAKER SHEETS

- ✓ STA-SET®
- ✓ ENDURA BRAID®
- ✓ POLY-TEC

8. SPINNAKER GUYS

- ✓ VPC
- ✓ ENDURA BRAID
- ✓ POLY-TEC

9. TACK LINE


- ✓ VPC
- ✓ ENDURA BRAID®
- ✓ POLY-TEC

10. REEF LINE

- ✓ STA-SET®
- ✓ VIPER-24
- ✓ ENDURA BRAID®

LEGEND

- ✓ good
- ✓ better
- ✓ best





Line	Percentage	Diameter										
	%		1/8" or 3mm	3/16" or 5mm	1/4" or 6mm	5/16" or 8mm	3/8" or 10mm	7/16" or 11mm	1/2" or 12mm	9/16" or 14mm	5/8" or 16mm	3/4" or 19mm
Sta-Set® / Sta-Set Solid®	2.80%	BREAKING STRENGTH (in pounds)	-	1,400	2,350	3,850	5,100	7,000	10,100	11,700	16,900	23,500
Regatta Braid	3.30%		-	-	2,550	3,300	4,800	6,500	8,000	12,400	-	-
Viper-24	0.65%		-	-	-	7,000	9,000	11,000	16,000	-	-	-
Poly-Tec	0.65%		-	2,800	5,590	8,840	13,100	-	19,440	21,900	-	-
VPC	1.40%		-	-	3,200	5,500	6,500	8,500	10,200	-	-	-
Endura Braid®	0.65%		-	1,860	4,500	8,100	10,200	14,900	21,500	25,200	-	-
HSR-75	0.60%		3,000	9,475	12,385	-	23,600	31,350	-	-	-	-
WR2 (Wire Rope Replacement)	0.65%		1,800	4,000	-	-	-	-	-	-	-	-
Spyderline	0.68%		1,250	3,000	-	-	-	-	-	-	-	-
Bzzz Line	3.25%		-	-	1,750	3,000	-	-	-	-	-	-
Vintage 3 Strand	9.00%		-	-	1,450	2,100	3,450	4,150	6,200	-	8,100	12,400
Dinghy Tow Line	5.00%		-	-	-	-	2,900	5,050	-	-	-	-
Nylon 3-Strand	12.00%		-	1,300	2,100	3,000	4,250	6,000	7,500	8,800	11,650	17,150
Premium 8 Plait	10.00%		-	-	-	-	-	-	8,000	-	-	-

LINE STRETCH IN THE REAL WORLD

Line stretch data

All line stretch data compiled from tests using 8mm rope. Illustration not drawn to scale.



8mm line at 500 lbs. of load

All High Techs (see inset)
VPC
Sta-Set®

High Tech Lines

SK-78 / SK-99
Endura Braid®
V-100
Viper-24

NEW ENGLAND ROPES®

established 1967



New Bedford, MA

ABOUT US

WHAT IS AN EXCITING BRAND FOR PLEASURE MARINE TODAY, STARTED 1967, IN NEW BEDFORD, MA, AS NEW ENGLAND ROPES®. BACK THEN IT WAS MAKING ITS SIGNATURE PRODUCT AT THE TIME, 3-STRAND PREMIUM NYLON. THE SAME PRODUCT IS PRODUCED TODAY TO THE SAME EXACTING STANDARDS. A HALF CENTURY LATER, THE BRAND IS STILL COMMITTED TO QUALITY, INNOVATION AND CONTINUOUS IMPROVEMENT.

INFORMATION


how to read this catalog sample outline



TYPE

Product Name

Description



Ø mm	Ø in	Length ft	BL Lbs.	Weight lbs/100	Color/Item no. white	red	green	blue	black	Designed and best used as:
5	3/16	600	1400	1.10	● 2090-06-00600	● 2101-06-00600	● 2102-06-00600	● 2103-06-00600	● 2084-06-00600	mainsheets, jib sheets, control lines
6	1/4	600	2350	12.00	● 2090-08-00600	● 2101-08-00600	● 2102-08-00600	● 2103-08-00600	● 2084-08-00600	

Cover: Polyester/Technora® 24 Core: HMPE®

Ø = diameter (mm)

The nominal diameter has tolerances in the plus and minus in millimeters.

Ø = diameter (in)

The nominal diameter has tolerances in the plus and minus in inches.

Length = rope length (ft)

The rope length per spool of coil in feet.

BL = breaking loads (Lbs.)

The value indicates the load at which the rope would break. The specified breaking loads are values determined in testing in our laboratory. In practical use, these values may deviate depending on the type of use. The breaking loads were determined for free lengths of rope and will be decreased by splices or knots. When defining a rope's dimensions, we recommend to apply a ratio of working load to breaking load of at least 1:5!

Weight = (lbs/100')

The specified values in pounds related to 100 feet of rope. The length of the rope can change during use. As a result, there may also be deviations from the specified weight.

Colors and order numbers

Example: the color "black" in 5mm has the Item no. 2084-06-00600 and is avail-

able for order.

IDENTIFICATION FIELD OF USE

RACING

This line is ideally suited for use as a halyard.

PERFORMANCE

Due to its low abrasion and minimal kink, this line is ideally suited for use as a sheet.

PERFORMANCE SINGLE BRAID

This line is suited for use as both a halyard and a sheet.

DINGHY/ONE DESIGN

This line can be used as a control line, or allround rope.

PERFORMANCE BRAIDS

These lines are designed for the rigors of competitive racing.

DOCKLINE

This line is suited for mooring all kinds of boats.

ANCHORING

This non-buoyant line is used for anchoring.

COMMERCIAL

Large diameter ropes engineered for commercial marine environments.

GOOD TO KNOW

Three symbols explain the availability of our products:

- available for order
- ⦿ ask your customer service for current availability
- as long as stock lasts / will not be restocked



New England Ropes® is
the Official Rope Partner
of US Sailing Team.



CONTENT

2 How to choose the Right Product

THE FOUR BASIC TYPES OF ROPE CONSTRUCTION.....	2
WHAT DO YOU NEED THIS LINE FOR?	2
BREAKING LOAD VS ELONGATION AT BREAK FIBER PROPERTIES.....	2

3 Elongation

4-5 Line Selection Guide

6 Line Recommendations

7 Line Stretch in the Real World

9 Information

12 Racing Boats

DYNEEMA CHAFE SLEEVE	13
HMPE CHAFE SLEEVE	13
POLY-TEC	14
POLY-TEC NATURALS	14
DYNA-TEC	15

16 Performance Racing

ENDURA BRAID®	17
ENDURA BRAID EURO®	17
ENDURA CLASSIC	18
V-100	18
T-900	18
NEW! - VIPER 24	19
VPC	19
NEW! - FLIGHT LINE	20
REGATTA LITE	20
ONE-DESIGN TOW LINE	20
NEXUS PRO	21
SALSA LINE	21

22 Performance Single Braids

HTS -78	23
ENDURA 12®	24-25
HTS-99	26
HSR	26
V-12	27
WR2 ULTRA	27

28 Dinghy One Design

MINI-V	29
POLY-TEC DINGHY	29
SPYDER LINE	29
FINISH LINE	30
NEW! - ENDLESS CONTROL	30
BZZZ LINE	30

31 Performance Braids

STA-SET® (SOLID)	32
VINTAGE STA-SET®	33
REGATTA BRAID	28

35 One Company – Infinite Possibilities

36 Dock and Anchor Lines

3-STRAND NYLON	37
DOUBLE BRAID NYLON	38
MEGA BRAID	39
MEGA BRAID II	39
MEGA PLAID	39
8-PLAIT	40
DINGHY TOW ROPE	40

42 3 Strand Traditional

3 STRAND CLASSIC POLYESTER	43
VINTAGE 3-STRAND	43
SPUN CLASSIC POLYESTER	44
SPUN POLYPROPYLENE	44
3-STRAND POLYPROPYLENE	45

48 Packaged Goods

PREMIUM 3 STRAND DOCKLINES	49
PREMIUM NYLON DOUBLE BRAID DOCKLINES ...	50
NYLON FENDER WHIPS	51
POLY/NYLON DOUBLE BRAID	51
MOORING PENDANT WITH STAINLESS THIMBLE	51
CYCLONE MOORING PENDANT	52
3-STRAND MOORING PENDANT	52
NYLON ANCHOR LINE	53
ROPE TO CHAIN ANCHOR RODES	53
MEGA PLAID ANCHOR RODES	54
MEGA PLAID TO CHAIN ANCHOR RODES	54
HOOK N MOOR	54
SOFT SHACKLES	55
WHIPPING TWINE	55

56 Cords and Accessories

BRAIDED POLYESTER CORD	57
T-100	57
HALYARD LEADER LINE	57
BRAIDED POLYESTER LUFFLINE	58
SHOCK CORD	58
NEW! HIGH TECH SHOCK CORD	58
ACCESSORIES	59

60 Commercial Marine

HOLDFAST	61
ENDURA-12	62
ENDURA BRAID®	62
NYLON DOUBLE BRAID	63
STA-SET®	63
POLY/NYLON DOUBLE BRAID	64
HYPERTEN	64
MULTILINE II	65
MEGA BRAID II	66
DA-PRO	66
T-12	67
V-12	67


RACING BOATS



©Omne van der Wal



OUR HIGH-TECH ROPES ARE DESIGNED
WITH THE RACER IN MIND TO PROVIDE
STRENGTH AND STRETCH RESISTANCE
WHEN AND WHERE YOU NEED IT MOST



RACING

Dyneema® Chafe Sleeve

This 48 carrier Dyneema® cover is perfect for use with high tech cores or twelve strands for high performance single braids. It is very tough and abrasion resistant and easily taperable for halyard ends.

Ø mm	Ø in	Length ft	BL Lbs.	Weight lbs/100	Color/Item no. white	Designed and best used as:
4-5	3/16	600		0.2	● C1930-04-00600	chafe sleeve, halyard ends, anywhere there will be extra wear
5-8	3/16	600		0.7	● C1930-06-00600	
8.5-11.5	5/16-3/8	300		1.01	● C1930-08-00300	
8.5-11.5	5/16-3/8	600		1.01	● C1930-08-00600	
12-16	1/2-5/8	600		1.40	● C1930-10-00600	

Cover: Dyneema®



RACING

HMPE Chafe Sleeve

This 48 carrier HMPE® (high molecular poly ethylene) cover is perfect for use with high tech cores or twelve strands for high performance single braids. It is very tough and abrasion resistant and easily taperable for halyard ends.

Ø mm	Ø in	Length ft	BL Lbs.	Weight lbs/100	Color/Item no. black	Designed and best used as:
4-5	3/16	600		0.2	● C1934-04-00600	chafe sleeve, halyard ends, anywhere there will be extra wear
4-5	3/16	300		0.2	● C1934-04-00300	
5-8	5/16-3/8	600		0.7	● C1934-06-00600	
5-8	5/16-3/8	300		0.7	● C1934-06-00300	
8.5-11.5	3/8-1/2	600		1.01	● C1934-08-00600	
8.5-11.5	3/8-1/2	300		1.01	● C1934-08-00300	
12-16	1/2-5/8	600		1.40	● C1934-10-00600	
12-16	1/2-5/8	300		1.40	● C1934-10-00300	
16-20	5/8-13/16	600		2.00	● C1934-12-00600	
16-20	5/8-13/16	300		2.00	● C1934-12-00300	

Cover: HMPE



RACING

Poly-Tec

Our Poly Tec offers excellent abrasion and heat dissipation with excellent cut resistance and a level of grip that other high tech fibers don't offer. Poly Tec cover can also be used with a variety of cores including our Endura-12® or V-12.



Ø mm	in	Length ft	BL Lbs.	Weight lbs/100	Color/Item no. black/blue	black/orange	black/red	black/yellow	Designed and best used as:
4.8	3/16	600	2,800	1.50	● C2983-04-00600	● C2985-04-00600	● C2981-04-00600	● C2986-04-00600	halyrds, mainsheets, genoa sheets, spinnaker sheets, tack lines, and control lines
6	1/4	600	5,590	3.00	● C2983-06-00600	● C2985-06-00600	● C2981-06-00600	● C2986-06-00600	
7	9/32	600	8,840	3.60	● C2983-07-00600	● C2985-07-00600	● C2981-07-00600	● C2986-07-00600	
8	5/16	600	8,840	4.20	● C2983-08-00600	● C2985-08-00600	● C2981-08-00600	● C2986-08-00600	
10	3/8	600	13,100	5.40	● C2983-10-00600	● C2985-10-00600	● C2981-10-00600	● C2986-10-00600	
12	1/2	600	19,440	6.60	● C2983-12-00600	● C2985-12-00600	● C2981-12-00600	● C2986-12-00600	
14	9/16	600	21,900	6.60	● C2983-14-00600	● C2985-14-00600	● C2981-14-00600	● C2986-14-00600	
Ø mm	in	Length ft	BL Lbs.	Weight lbs/100	Color/Item no. black/green	black/pink	black/purple		
4.8	3/16	600	2,800	1.50	● C2982-04-00600	● C298E-04-00600	● C2989-04-00600		
6	1/4	600	5,590	3.00	● C2982-06-00600	● C298E-06-00600	● C2989-06-00600		
7	9/32	600	8,840	3.60	● C2982-07-00600	● C298E-07-00600	● C2989-07-00600		
8	5/16	600	8,840	4.20	● C2982-08-00600	● C298E-08-00600	● C2989-08-00600		
10	3/8	600	13,100	5.40	● C2982-10-00600	● C298E-10-00600	● C2989-10-00600		
12	1/2	600	19,440	6.60	● C2982-12-00600	● C298E-12-00600	● C2989-12-00600		
14	9/16	600	21,900	6.60	● C2982-14-00600	● C298E-14-00600	● C2989-14-00600		

Cover: Polyester/Technora® 24 Core: Dyneema®



RACING


Poly-Tec Naturals

Our Poly Tec offers excellent abrasion and heat dissipation with excellent cut resistance and a level of grip that other high tech fibers don't offer. The Poly Tec cover can also be used with a variety of cores including our Endura-12® or V-12.



Ø mm	in	Length ft	BL Lbs.	Weight lbs/100	Color/Item no. red/natural	green/natural	blue/natural	black/natural	Designed and best used as:
6	1/4	600	5,590	3.00	● C2991-06-00600	-	-		halyrds, mainsheets, genoa sheets, spinnaker sheets, tack lines, and control lines
7	9/32	600	8,840	3.60	● C2991-07-00600	-	● C2993-06-00600		
8	5/16	600	8,840	4.20	● C2991-08-00600	● C2992-08-00600	● C2993-08-00600	● C2994-08-00600	
10	3/8	600	13,100	5.40	● C2991-10-00600	-	● C2993-10-00600		
12	1/2	600	21,700	6.60	● C2991-12-00600	-	● C2993-12-00600		


Cover: Polyester/Technora® 24 Core: Dyneema®



RACING

Dyna-Tec

Dyna-Tec is constructed with the ideal balance of Dyneema®, Technora®, polyester, and Dyneema® fibers. Offering excellent abrasion resistance, heat dissipation and cut resistance as well as a lower friction coefficient, Dyna-Tec yields the optimum levels of performance.



Ø		Length	BL	Weight	Color/Item no.				Designed and best used
mm	in	ft	Lbs.	lbs/100	red	green	blue	black	
7	9/32	600	5000	45	● C2681-07-00600	● C2682-07-00600	● C2683-07-00600	● C2684-07-00600	mainsheets, genoa sheets, spinnaker sheets, and control lines
8	5/16	600	8200	72	● C2681-08-00600	● C2682-08-00600	● C2683-08-00600	● C2684-08-00600	
10	3/8	600	13900	101	● C2681-10-00600	● C2682-10-00600	● C2683-10-00600	● C2684-10-00600	
12	1/2	600	16100	132	● C2681-12-00600	● C2682-12-00600	● C2683-12-00600	● C2684-12-00600	

Cover: Dyneema®, Technora, polyester Core: HTS 78



Viper 24. Photo Credit: Peter Phelan, New England Ropes

PERFORMANCE RACING



BUILT AND TESTED BY PROFESSIONALS
NEW ENGLAND ROPES® UNDERSTANDS
WHAT SAILORS DEMAND FROM THEIR
GEAR. THAT'S WHY WE PROUDLY SUPPORT
THE US SAILING TEAM.



PERFORMANCE


Endura Braid®

Performance, strength, and durability, Endura Braid® features a specially engineered 12-strand Dyneema® core, with marine-tech coating, and a 24 carrier braided polyester cover that was created with the competitive sail-or in mind. Benefits include a very high strength-to-weight ratio, very low stretch, low creep and outstanding durability. Its coated braided core is ideal for durable, tapered sheets and halyards.



Ø mm in	Length ft	BL Lbs.	Weight lbs/100	Color/Item no. white	green	blue	black	red	Designed and best used as:
6 1/4	600	4,500	1.80	● C2510-06-00600	● C2522-06-00600	● C2523-06-00600	-	● C2521-06-00600	sheets, halyards, tack lines, topping lifts, reef lines, and control lines, works well in clutches
8 5/16	600	8,100	3.00	● C2510-08-00600	-	● C2523-08-00600	● C2524-08-00600	● C2521-08-00600	
10 3/8	600	10,200	3.80	● C2510-10-00600	● C2522-10-00600	● C2523-10-00600	● C2524-10-00600	● C2521-10-00600	
11 7/16	600	14,900	5.40	-	● C2522-11-00600	● C2523-11-00600	● C2524-11-00600	● C2521-11-00600	
12 1/2	600	21,500	6.60	○ C2510-12-00600	-	○ C2523-12-00600	-	○ C2521-12-00600	

Cover: 24 carrier Polyester Core: Dyneema®



PERFORMANCE

Endura Braid® Euro

Endura Braid® Euro Style utilizes a mottled cover design and was developed in conjunction with leading riggers worldwide and was tested in the harshest of conditions. The result was that it surpassed the standards of performance time and again. Endura Braid® Euro Style features a Dyneema® 12-strand core.



Ø mm in	Length ft	BL Lbs.	Weight lbs/100	Color/Item no. white	red	green	Designed and best used as:
4 5/32	600	1,860	0.85	● C2500A-04-00600	C2501A-04-00600	C2502A-04-00600	all running rigging, sheets, halyards, tack lines, topping lifts, reef lines or where low-stretch control is needed. works well in clutches
5 3/16	600	3,100	1.10	● C2500A-05-00600	● C2501A-05-00600	● C2502A-05-00600	
6 1/4	600	4,500	1.80	● C2500A-06-00600	● C2501A-06-00600	● C2502A-06-00600	
8 5/16	600	8,100	3.00	● C2500A-08-00600	● C2501A-08-00600	● C2502A-08-00600	
10 3/8	600	10,200	3.80	○ C2500A-10-00600	● C2501A-10-00600	● C2502A-10-00600	
11 7/16	600	14,900	5.40	● C2500A-11-00600	● C2501A-11-00600	● C2502A-11-00600	
12 1/2	600	21,500	6.60	● C2500A-12-00600	● C2501A-12-00600	● C2502A-12-00600	
14 9/16	600	25,200	8.60	● C2500A-14-00600	● C2501A-14-00600	● C2502A-14-00600	
Ø mm in	Length ft	BL Lbs.	Weight lbs/100	Color/Item no. blue	black	yellow	
4 5/32	600	1,860	0.85	C2503A-04-00600	C2504A-04-00600	○	
5 3/16	600	3,100	1.10	● C2503A-05-00600	● C2504A-05-00600	○	
6 1/4	600	4,500	1.80	● C2503A-06-00600	● C2504A-06-00600	● C2506C-06-00600	
8 5/16	600	8,100	3.00	● C2503A-08-00600	● C2504A-08-00600	● C2506C-08-00600	
10 3/8	600	10,200	3.80	● C2503A-10-00600	- C2504A-10-00600	● C2506C-10-00600	
11 7/16	600	14,900	5.40	● C2503A-11-00600	● C2504A-11-00600	● C2506C-11-00600	
12 1/2	600	21,500	6.60	● C2503A-12-00600	● C2504A-12-00600	● C2506C-12-00600	
14 9/16	600	25,200	8.60	● C2503A-14-00600	● C2504A-14-00600	○	

Cover: 24 carrier Polyester Core: Dyneema®



PERFORMANCE

Endura Classic

The perfect compliment of high performance and classic look and feel for the traditional vessel, Endura Classic has a specially engineered 12-strand Dyneema® core with marine-tech coating along with a 24 carrier braided polyester cover with spun fiber for extra grip, which is available in a classic color.

Ø mm in	Length ft	BL Lbs.	Weight lbs/100	Color/Item no. natural tan	Designed and best used as:
8 5/16	600	7,900	2.90	● C249CC-08-00600	sheets, halyards, guys, topping lifts, and reef lines, works well in clutches
11 7/16	600	10,500	4.50	● C249CC-11-00600	
12 1/2	600	15,400	5.45	● C249CC-12-00600	
13 17/32	600	21,800	6.65	● C249CC-13-00600	


Cover: 24 carrier Polyester Core: Dyneema®



PERFORMANCE

V-100

The ultimate in high load performance, V-100 features a braided 100% Vectran® 12-strand single braid core treated with our unique marine-tech coating with a highly durable and attractive polyester cover. V-100 is a very strong, low stretch, high-tech line for its size and it has good abrasion resistance and virtually no creep.



Ø mm in	Length ft	BL Lbs.	Weight lbs/100	Color/Item no. white	red	green	blue	black	Designed and best used as:
6 1/4	600	4,600	2.10	● C2820-06-00600	● C2821-06-00600	● C2822-06-00600	● C2823-06-00600	● C2824-06-00600	mainsheets, genoa sheets, runners
8 5/16	600	8,600	3.50	● C2820-06-00600	● C2821-06-00600	● C2822-06-00600	● C2823-06-00600	● C2824-06-00600	
10 3/8	600	12,600	5.30	● C2820-06-00600	● C2821-06-00600	● C2822-06-00600	● C2823-06-00600	● C2824-06-00600	
11 7/16	600	17,200	6.50	● C2820-06-00600	● C2821-06-00600	● C2822-06-00600	● C2823-06-00600	● C2824-06-00600	
12 1/2	600	19,200	7.10	● C2820-06-00600	● C2821-06-00600	● C2822-06-00600	● C2823-06-00600	● C2824-06-00600	


Cover: Polyester 32 Core: Vectran®



PERFORMANCE

T-900

A low stretch and low creep line, T-900 features our pioneering blend of Dyneema® and Technora® in its core with a durable polyester cover. A combination of high strength, low weight plus low creep, T-900 is an excellent choice for static loads and is a more economical option to V-100.



Ø mm in	Length ft	BL Lbs.	Weight lbs/100	Color/Item no. white	red fleck	green fleck	blue fleck	Designed and best used as:
8 5/16	200	5000	45	● C2750-08-00600	● C2761-08-00600	● C2762-08-00600	● C2763-08-00600	halyards on catamaras, long distance cruising static halyards
10 3/8	200	8200	72	● C2750-10-00600	● C2761-10-00600	● C2762-10-00600	● C2763-10-00600	
11 7/16	170	13900	101	● C2750-11-00600	● C2761-11-00600	● C2762-11-00600	● C2763-11-00600	
12 1/2	200	16100	132	-	● C2761-12-00600	● C2762-12-00600	● C2763-12-00600	
14 9/16				● C2750-14-00600	-	-	-	


Cover: Polyester 32 Core: Dyneema® and Technora



PERFORMANCE

NEW! - Viper 24

Viper is the latest intro into performance cordage from New England Ropes®. Viper has a 24 carrier braided polyester cover over our proprietary HMPE core material. The braided and coated HMPE core was engineered to be lightweight, with very low stretch and provides good UV resistance.



FIND OUT MORE:



Ø		Length	BL	Weight	Color/Item no.					Designed and best used as:
mm	in	ft	Lbs.	lbs/100	red	green	blue	black	yellow	
8	5/16	600	7,000	2.89	● C2271-08-00600	● C2272-08-00600	● C2273-08-00600	● C2274-08-00600	● C2276-08-00600	mainsheets, jib sheet, spinnaker sheet, halyards, foreguy, tack line, and clutches
10	3/8	600	9,000	4.84	● C2271-10-00600	● C2272-10-00600	● C2273-10-00600	● C2274-10-00600	● C2276-10-00600	
11	7/16	600	11,000	5.62	● C2271-11-00600	● C2272-11-00600	● C2273-11-00600	● C2274-11-00600	● C2276-11-00600	
12	1/2	600	16,000	6.55	● C2271-12-00600	● C2272-12-00600	● C2273-12-00600	● C2274-12-00600	● C2276-12-00600	

Cover: 24 carrier Polyester Core: HMPE®



PERFORMANCE

VPC

VPC is a unique mid-tech product for sheets and halyards, utilizing hybrid performance technology. It features a strong blended Vectran® and polyolefin core with a durable polyester cover. VPC fills the gap between performance polyester lines and ultra high performance racing lines.



Ø	Length	BL	Weight	Color/Item no.	white	solid red	solid green	solid blue	Designed and best used as:
mm	m	Lbs.	lbs/100'						
6	600	3,200	13	-		● C2831-06-00600	● C2832-06-00600	● C2833-06-00600	mainsheets, jib sheets, halyards
8	600	5,500	25	● C2830-08-00600		● C2831-08-00600	● C2832-08-00600	● C2833-08-00600	
10	600	6,500	36	● C2830-10-00600		● C2831-10-00600	● C2832-10-00600	● C2833-10-00600	
11	600	8,500	43	● C2830-11-00600		● C2831-11-00600	● C2832-11-00600	● C2833-11-00600	
12	600	10,200	46	● C2830-12-00600		● C2831-12-00600	● C2832-12-00600	● C2833-12-00600	
Ø	Length	BL	Weight	Color/Item no.	red fleck	green fleck	blue fleck		
mm	m	Lbs.	g/m						
6	600	3,200	13	● C2841-06-00600	● C2842-06-00600	● C2843-06-00600			
8	600	5,500	25	● C2841-08-00600	● C2842-08-00600	● C2843-08-00600			
10	600	6,500	36	● C2841-10-00600	● C2842-10-00600	● C2843-10-00600			
11	600	8,500	43	● C2841-11-00600	● C2842-11-00600	● C2843-11-00600			
12	600	10,200	46	● C2841-12-00600	● C2842-12-00600	● C2843-12-00600			

Cover: Polyester Core: Vectran® and MFP

NEW!



PERFORMANCE

NEW! - Flight Line

Flight Line is a strong, lightweight, flexible, low-stretch line with a braided core that is easily tapered and it floats. It's soft on the hands and gets even softer with use and is available in new mottled coloring



Ø	Length	BL	Weight	Color/Item no.					Designed and best used
mm	in	ft	Lbs.	lbs/100	red	green	blue	purple	as:
4	1/4	600	2,500	1.40	● C2431-06-00600	● C2432-06-00600	● C2433-06-00600	● C2439-06-00600	light air spinnaker sheets and dinghy/one design control lines
5	5/16	600	4,000	2.20	● C2431-08-00600	● C2432-08-00600	● C2433-08-00600	-	
9.5	3/8	600	4,700	3.20	● C2431-09-00600	● C2432-09-00600	-	-	

Cover: Polypropylene Core: Dyneema®



PERFORMANCE


Regatta Lite

Lightweight and great to handle, Regatta Lite is a 12-strand, single braid, multifilament polypropylene line that is extremely lightweight (either wet or dry), does not kink, and is easy to handle.



Ø	Length	BL	Weight	Color/Item no.				Designed and best used
mm	in	ft	Lbs.	lbs/100	purple	teal	yellow	as:
6	1/4	600	1,050	1.30	● C1274-06-00600	● C1277-06-00600	-	dinghy, small keel boat, mainsheets, and control lines
8	5/16	600	2,560	2.20	● C1274-08-00600	● C1277-08-00600	● C1276-08-00600	
9	3/8	600	3,200	2.90	-	● C1277-09-00600	● C1276-09-00600	


Single Braid: polypropylene



PERFORMANCE

One-Design Tow Line

Buoyant, lightweight line that's perfect for small one-design Bow/Tow Lines. One-Design Tow Line is a braided 16-plait of XLF fibers that allow it to float easily. It's round, firm shape, is ideal for handling and tying a knot for security. Easily visible in water and does not absorb water.



Ø	Length	BL	Weight	Color/Item no.			Designed and best used
mm	in	ft	Lbs.	lbs/100	orange w/blue tracer	yellow w/red tracer	as:
6	1/4	660	1,050	1.30	● 7151524	-	tow line for racing dinghys, Code 0, and asymmetrical spinnaker retrieval lines
8	5/16	660	2,560	2.20	● 7151525	● 7153081	
10	3/8	660	3,200	2.90	● 7151523	-	

Single Braid: polypropylene



PERFORMANCE

Nexus Pro

This innovation from New England Ropes®, Nexus Pro has been developed in cooperation with our competitive sports partners and sailors. It is now the gold standard for performance-minded sailors. Nexus Pro has a durable, lightweight cover that offers excellent grip and holding power. The core is pure Dyneema® for ultra-strength and lowstretch and is easily strippable.



Ø	Ø	Length	BL	Weight	Color/Item no.				Designed and best used
mm	in	ft	Lbs.	lbs/100	red	blue	black	yellow	as:
5	3/16	600	2,500	0.97	● C2641-05-00600	● C2643-05-00600	● C2644-05-00600	● C2646-05-00600	spinnaker sheets and halyards on sports boats works well in clam clutches, vang, control lines
6	1/4	600	3,600	1.15	● C2641-06-00600	● C2643-06-00600	● C2644-06-00600	● C2646-06-00600	
7	9/32	600	6,000	1.75	● C2641-07-00600	● C2643-07-00600	● C2644-07-00600	● C2646-07-00600	
8	5/16	600	7,300	2.40	○ C2641-08-00600	○ C2643-08-00600	○ C2644-08-00600	○ C2646-08-00600	
10	3/8	600	11,000	3.40	○ C2641-10-00600	○ C2643-10-00600	○ C2644-10-00600	○ C2646-10-00600	


Cover: Polyester/Technora® Core: Dyneema®



PERFORMANCE

Salsa Line

Salsa Line is ultra strong, ultra soft, and the perfect sheet for larger one designs and keelboats. Your hands will love this soft and exceptionally strong single braid constructed of Dyneema® and spun filament polyester.



Ø	Ø	Length	BL	Weight	Color/Item no.				Designed and best used
mm	in	ft	Lbs.	lbs/100	yellow	grey	red-white-blue		as:
6	1/4	600	2,850	1.80	● C1682-06-00600	● C1688-06-00600	● C1687-06-00600		mainsheets, spinnaker sheets
8	5/16	600	4,000	2.90	● C1682-08-00600	● C1688-08-00600	● C1687-08-00600		
9.5	3/8	600	5,000	3.50	-	● C1688-09-00600	-		

Single Braid: Polyester and Dyneema®

PERFORMANCE SINGLE BRAIDS



© Allison Chenard, US Sailing



OUR WIRE REPLACEMENT LINES HELP YOU
TO MAINTAIN PERFORMANCE AND SAVE
CRITICAL POUNDS ON THE WATER WHILE
PROVIDING A STRONGER THAN STEEL
TENSILE STRENGTH TO KEEP YOUR SAILS
TIGHT.



PERFORMANCE SINGLE BRAID

HTS -78

Very high strength, low stretch, ultra low creep, HTS-78 features 100% Dyneema® fiber. This 12-strand single braid is treated with our unique marine-tech coating for excellent abrasion and uv resistance. This ultra low creep line yields the highest levels of performance, time and again.



Ø mm	Ø in	Length ft	BL Lbs.	Weight lbs/100	Color/Item no. white	red	blue	Designed and best used as:
2	3/32	600	1,000	0.20	● C1420-02-00600	● C1421-02-00600	● C1423-02-00600	cascade lines, halyards, wire rope replacement, cunninghams, vang systems
2.5	7/64	600	1,800	0.30	● C1420-03-00600	● C1421-03-00600	● C1423-03-00600	
3	1/8	600	2,800	0.50	● C1420-04-00600	● C1421-04-00600	● C1423-04-00600	
4	5/32	600	4,300	0.65	● C1420-05-00600	● C1421-05-00600	● C1423-05-00600	
5	3/16	600	6,050	1.20	● C1420-06-00600	● C1421-06-00600	● C1423-06-00600	
6	1/4	600	9,700	1.70	● C1420-08-00600	● C1421-08-00600	● C1423-08-00600	
8	5/16	600	14,500	2.55	● C1420-10-00600	● C1421-10-00600	● C1423-10-00600	
10	3/8	600	18,800	3.40	● C1420-12-00600	● C1421-12-00600	● C1423-12-00600	
11	7/16	600	24,000	4.20	● C1420-14-00600	● C1421-14-00600	● C1423-14-00600	
12	1/2	600	34,300	6.15	● C1420-16-00600	● C1421-16-00600	● C1423-16-00600	

Single Braid Dyneema® SK-78

Ø mm	Ø in	Length ft	BL Lbs.	Weight lbs/100	black	orange	grey	Designed and best used as:
2	3/32	600	1,000	0.20	● C1424-02-00600	● C1425-02-00600	● C1428-02-00600	cascade lines, halyards, wire rope replacement, cunninghams, vang systems
2.5	7/64	600	1,800	0.30	● C1424-03-00600	● C1425-03-00600	● C1428-03-00600	
3	1/8	600	2,800	0.50	● C1424-04-00600	● C1425-04-00600	● C1428-04-00600	
4	5/32	600	4,300	0.65	● C1424-05-00600	● C1425-05-00600	● C1428-05-00600	
5	3/16	600	6,050	1.20	● C1424-06-00600	● C1425-06-00600	● C1428-06-00600	
6	1/4	600	9,700	1.70	● C1424-08-00600	● C1425-08-00600	● C1428-08-00600	
8	5/16	600	14,500	2.55	● C1424-10-00600	● C1425-10-00600	● C1428-10-00600	
10	3/8	600	18,800	3.40	● C1424-12-00600	● C1425-12-00600	● C1428-12-00600	
11	7/16	600	24,000	4.20	● C1424-14-00600	● C1425-14-00600	● C1428-14-00600	
12	1/2	600	34,300	6.15	● C1424-16-00600	● C1425-16-00600	● C1428-16-00600	

Single Braid Dyneema® SK-78



PERFORMANCE SINGLE BRAID

Endura 12®

Low stretch and very high strength, Endura 12® features 100% Dyneema® fiber. This 12-strand single braid is treated with our unique marine-tech coating for excellent abrasion and uv resistance.



Ø mm	Ø in	Length ft	BL Lbs.	Weight lbs/100	Color/Item no. black	orange	yellow	fluorescent green	gray
2	3/32	600	1,000	0.20	● C1524-02-00600	● C1525-02-00600	● C1526-02-00600	● C1527-02-00600	● C1528-02-00600
2.5	7/64	600	1,800	0.30	● C1524-03-00600	● C1525-03-00600	● C1526-03-00600	● C1527-03-00600	● C1528-03-00600
3	1/8	600	2,800	0.50	● C1524-04-00600	● C1525-04-00600	● C1526-04-00600	● C1527-04-00600	● C1528-04-00600
4	5/32	600	4,300	0.65	○ C1524-05-00600	○ C1525-05-00600	○ C1526-05-00600	○ C1527-05-00600	○ C1528-05-00600
5	3/16	600	6,050	1.20	● C1524-06-00600	● C1525-06-00600	● C1526-06-00600	● C1527-06-00600	● C1528-06-00600
6	1/4	600	9,700	1.70	● C1524-08-00600	● C1525-08-00600	● C1526-08-00600	● C1527-08-00600	● C1528-08-00600
8	5/16	600	14,500	2.55	● C1524-10-00600	● C1525-10-00600	● C1526-10-00600	● C1527-10-00600	● C1528-10-00600
10	3/8	600	18,800	3.40	● C1524-12-00600	● C1525-12-00600	● C1526-12-00600	● C1527-12-00600	● C1528-12-00600
11	7/16	600	24,000	4.20	● C1524-14-00600	● C1525-14-00600	● C1526-14-00600	● C1527-14-00600	● C1528-14-00600
12	1/2	600	34,300	6.15	● C1524-16-00600	● C1525-16-00600	● C1526-16-00600	● C1527-16-00600	● C1528-16-00600
14	9/16	600	42,000	7.20	● C1524-18-00600	● C1525-18-00600	● C1526-18-00600	● C1527-18-00600	● C1528-18-00600
16	5/8	600	58,000	10.10	● C1524-20-00600	● C1525-20-00600	● C1526-20-00600	● C1527-20-00600	● C1528-20-00600
18	3/4	600	67,700	14.74	● C1524-24-00600	● C1525-24-00600	● C1526-24-00600	● C1527-24-00600	● C1528-24-00600
22	7/8	600	97,500	18.80	● C1524-28-00600	● C1525-28-00600	● C1526-28-00600	● C1527-28-00600	● C1528-28-00600
24	1	600	114,000	23.40	● C1524-32-00600	● C1525-32-00600	● C1526-32-00600	● C1527-32-00600	● C1528-32-00600
28	1 1/8	600	148,000	31.00	● C1524-36-00600	● C1525-36-00600	● C1526-36-00600	● C1527-36-00600	● C1528-36-00600
30	1 1/4	600	171,000	36.60	● C1524-40-00600	● C1525-40-00600	● C1526-40-00600	● C1527-40-00600	● C1528-40-00600
32	1 5/16	600	190,000	40.50	● C1524-42-00600	● C1525-42-00600	● C1526-42-00600	● C1527-42-00600	● C1528-42-00600
34	1 3/8	600	212,000	45.40	● C1524-44-00600	● C1525-44-00600	● C1526-44-00600	● C1527-44-00600	● C1528-44-00600
36	1 1/2	600	228,000	48.80	● C1524-50-00600	● C1525-50-00600	● C1526-50-00600	● C1527-50-00600	● C1528-50-00600

Single Braid Dyneema® SK-75



PERFORMANCE SINGLE BRAID

Endura 12®

Low stretch and very high strength, Endura 12® features 100% Dyneema® fiber. This 12-strand single braid is treated with our unique marine-tech coating for excellent abrasion and uv resistance.



Ø		Length	BL	Weight	Color/Item no.				Designed and best used
mm	in	ft	Lbs.	lbs/100	white	red	green	blue	as:
2	3/32	600	1,000	0.20	● C1520-02-00600	● C1521-02-00600	● C1522-02-00600	● C1523-02-00600	cascade lines, hyalyards, wire rope replacement, cunninghams, vang systems
2.5	7/64	600	1,800	0.30	● C1520-03-00600	● C1521-03-00600	● C1522-03-00600	● C1523-03-00600	
3	1/8	600	2,800	0.50	● C1520-04-00600	● C1521-04-00600	● C1522-04-00600	● C1523-04-00600	
4	5/32	600	4,300	0.65	○ C1520-05-00600	○ C1521-05-00600	○ C1522-05-00600	○ C1523-05-00600	
5	3/16	600	6,050	1.20	● C1520-06-00600	● C1521-06-00600	● C1522-06-00600	● C1523-06-00600	
6	1/4	600	9,700	1.70	● C1520-08-00600	● C1521-08-00600	● C1522-08-00600	● C1523-08-00600	
8	5/16	600	14,500	2.55	● C1520-10-00600	● C1521-10-00600	● C1522-10-00600	● C1523-10-00600	
10	3/8	600	18,800	3.40	● C1520-12-00600	● C1521-12-00600	● C1522-12-00600	● C1523-12-00600	
11	7/16	600	24,000	4.20	● C1520-14-00600	● C1521-14-00600	● C1522-14-00600	● C1523-14-00600	
12	1/2	600	34,300	6.15	● C1520-16-00600	● C1521-16-00600	● C1522-16-00600	● C1523-16-00600	
14	9/16	600	42,000	7.20	● C1520-18-00600	● C1521-18-00600	● C1522-18-00600	● C1523-18-00600	
16	5/8	600	58,000	10.10	● C1520-20-00600	● C1521-20-00600	● C1522-20-00600	● C1523-20-00600	
18	3/4	600	67,700	14.74	● C1520-24-00600	● C1521-24-00600	● C1522-24-00600	● C1523-24-00600	
22	7/8	600	97,500	18.80	● C1520-28-00600	● C1521-28-00600	● C1522-28-00600	● C1523-28-00600	
24	1	600	114,000	23.40	● C1520-32-00600	● C1521-32-00600	● C1522-32-00600	● C1523-32-00600	
28	1 1/8	600	148,000	31.00	● C1520-36-00600	● C1521-36-00600	● C1522-36-00600	● C1523-36-00600	
30	1 1/4	600	171,000	36.60	● C1520-40-00600	● C1521-40-00600	● C1522-40-00600	● C1523-40-00600	
32	1 5/16	600	190,000	40.50	● C1520-42-00600	● C1521-42-00600	● C1522-42-00600	● C1523-42-00600	
34	1 3/8	600	212,000	45.40	● C1520-44-00600	● C1521-44-00600	● C1522-44-00600	● C1523-44-00600	
36	1 1/2	600	228,000	48.80	● C1520-50-00600	● C1521-50-00600	● C1522-50-00600	● C1523-50-00600	

Single Braid Dyneema® SK-75



PERFORMANCE SINGLE BRAID

HTS-99

Ultra-light and exceptionally strong, HTS-99 utilizes 100% Dyneema® SK-99 fiber. The use of this high modulus fiber results in increased strength and excellent creep resistance.

Ø mm in	Length ft	BL daN	Weight lbs/100	Color/Item no. black	Designed and best used as:
1	600	600	0.08	● C1394-01-00600	halyards, vang systems, low stretch applications
2	³ / ₃₂	600	2,000	0.24	● C1394-02-00600
3	¹ / ₈	600	3,500	0.40	● C1394-03-00600
4	⁵ / ₃₂	600	5,200	0.61	● C1394-04-00600
5	³ / ₁₆	600	7,250	1.40	● C1394-05-00600
6	¹ / ₄	600	14,000	1.71	● C1394-06-00600

Single Braid Dyneema® SK-99



PERFORMANCE SINGLE BRAID

HSR Stronger than Steel®

Comprised of Dyneema® fiber, Stronger Than Steel® HSR is heat-set which at a microscopic level reorients the molecular chains in a linear fashion, thus ensuring greater load bearing capacity throughout the rope. The process of heating the rope under tension in combination with the longer braid angle results in an extremely strong, stiff line ideal for wire replacement applications or where stretch is not an option

Ø mm	in	Length ft	BL Lbs.	Weight lbs/100	Color/Item no. silver	Designed and best used as:
3	⁵ / ₃₂	660	3,000	0.45	● C1628-03-00660	replaces wire trapeeze lines, trailer winches, towing, davitt systems, life lines
4	³ / ₁₆	660	5,200	0.60	● C1628-04-00660	
5	¹ / ₄	660	9,475	1.30	● C1628-05-00660	
6	⁵ / ₁₆	660	12,385	1.70	● C1628-06-00660	
7	³ / ₈	660	18,700	2.50	● C1628-07-00660	
9	⁷ / ₁₆	660	23,600	3.95	● C1628-09-00660	
11	¹ / ₂	660	31,530	5.10	● C1628-11-00660	

Single Braid Dyneema®



PERFORMANCE SINGLE BRAID

V-12

This 12 strand line has little to no creep and is made with 100% Vectran® fibers. Coated with marine-tech for abrasion resistance and UV protection, this line has a tighter bend radius than other similar types of line and is also heat resistant.

Ø mm in	Length ft	BL Lbs.	Weight lbs/100	Color/Item no. clear	Designed and best used as:
3 1/8	600	2,100	0.46	● C1460-03-00600	performance oriented sheet under deck control lines
4 5/32	600	3,300	0.80	● C1460-04-00600	
5 3/16	600	4,950	1.20	● C1460-05-00600	
6 1/4	600	7,200	1.50	● C1460-06-00600	
10 3/8	600	17,000	4.70	● C1460-10-00600	


Single Braid Vectran®



GRAND PRIX

WR2 Ultra

WR2 (Wire Rope Replacement) Ultra is designed as a wire rope replacement. It's core is pre-stretched using our proprietary Stronger Than Steel® Technology and it's protective sheath is comprised of Dyneema® that is coated for increased UV resistance and cover/core bonding.




Ø mm in	Length ft	BL Lbs.	Weight lbs/100	Color/Item no. white	gray	orange	yellow	green	Designed and best used as:
3 1/8	600	1,800	0.39	● C2720-03-00600	● C2728-03-00600	● C2725-03-00600	● C2726-03-00600	● C2727-03-00600	life lines, control lines, traveler line [5mm] ILCA works well in clam cleats, trapeze control line
4 5/32	600	3,670	0.75	● C2720-04-00600	● C2728-04-00600	● C2725-04-00600	● C2726-04-00600	● C2727-04-00600	
5 3/16	600	4,000	1.15	● C2720-05-00600	● C2728-05-00600	● C2725-05-00600	● C2726-05-00600	● C2727-05-00600	
7 9/32	600	7,400	1.85	● C2720-07-00600	● C2728-07-00600	● C2725-07-00600	● C2726-07-00600	● C2727-07-00600	

Cover: 32 Carrier Dyneema® Core: Dyneema® SK78

DINGHY ONE DESIGN




UNDERSTANDING THE NEEDS FOR
DIFFERENT RACE CONDITIONS AND
HANDLING, NEW ENGLAND ROPES®
OFFERS A NUMBER OF SOLUTIONS FOR
RACERS OF ALL SKILL LEVELS



ONE-DESIGN


Mini-V

Mini V has a tight polyester cover and a flexible Vectran® core. It is ideally suited for dinghy control lines where a high strength to size ratio is needed along with low stretch, no creep, and excellent knotability.



Ø mm	in	Length ft	BL Lbs.	Weight lbs/100	Color/Item no. red	black	yellow	Designed and best used as:
2	3/32	300	270	0.20	● C2801-02-00300	● C2804-02-00300	● C2806-02-00300	dinghy vang, sail ties, lashings
3	1/8	300	930	0.40	● C2801-03-00300	● C2804-03-00300	● C2806-03-00300	
4	5/32	300	1,440	0.90	● C2801-04-00300	● C2804-04-00300	● C2806-04-00300	

Cover: Polyester Core: Vectran®



ONE-DESIGN

Poly-Tec Dinghy

Poly Tec Dinghy Range is the ideal balance of Technora® and polyester fibers, engineered to the demanding standards of riggers worldwide. Poly Tec Dinghy Range offers excellent abrasion and heat dissipation, excellent cut resistance, and a level of grip that other high tech fibers just don't offer.



Ø mm	in	Length ft	BL Lbs.	Weight lbs/100	Color/Item no. yellow-white	neon orange	blue-black	orange-black	Designed and best used as:
4	5/32	328	1,100	1.20	● 7156413	● 7156414			winches with abrasive surfaces (ceramic or new performance winches)
5	3/16	328	2,700	1.50	● 7156411	● 7156412	● 7156411	● 7150222	

Cover: Polyester/Technora® Core: Dyneema®



ONE-DESIGN


Spyder Line

This dinghy control line got its name because of its spider web-like strength thanks to its Dyneema® core and twill pattern (smooth) cover. Spyder Line is just the right small diameter line needed for higher load applications. It is very strong and low stretch, and is flexible yet firm enough to be fed through small leads, micro blocks, and purchase systems. Sizes over 1.8mm have a braided core, allowing for additional performance modifications.



Ø mm	in	Length ft	BL Lbs.	Weight lbs/100	Color/Item no. red	lime green	black	mango	purple	Designed and best used as:
1.8	1/16	500	350	0.20	● C2971-02-00500	● C2972-02-00500	● C2974-02-00500	● C2976-02-00500	● C2979-02-00500	outhaul, vang, cunningham, control lines, halyards
2.8	1/8	300	1,250	0.50	● C2971-03-00300	● C2972-03-00300	● C2974-03-00300	● C2976-03-00300	● C2979-03-00300	
3.8	5/32	300	1,860	0.85	● C2971-04-00300	● C2972-04-00300	● C2974-04-00300	● C2976-04-00300	● C2979-04-00300	
4.8	3/16	300	3,000	1.40	● C2971-05-00300	● C2972-05-00300	● C2974-05-00300	● C2976-05-00300	● C2979-05-00300	

Cover: Twill Core: Dyneema®




ONE-DESIGN

Finish Line

Strong and lightweight sheets, perfect for tapering, Finish Line will certainly take-off with its lightweight, non-absorbent xlf cover and its 100% braided Dyneema® core.

Finish Line is a strong, lightweight, flexible, low-stretch line with a braided core that is easily tapered. It's soft on the hands and gets even softer with use.



Ø mm	in	Length ft	BL Lbs.	Weight lbs/100	Color/Item no. white fleck	red	blue	grey	Designed and best used as:
3	1/8	600	500	0.60	● C3680-03-00600	● C3681-03-00600	-	● C3688-03-00600	dinghy outhauls, vang systems, cunnings, hanks, hiking strap lines, centerboard lines, topping lifts and halyards
4	5/32	600	920	0.80	● C3680-04-00600	● C3681-04-00600	● C3683-04-00600	● C3688-04-00600	
5	3/16	600	1,550	1.30	● C3680-05-00600	● C3681-05-00600	● C3683-05-00600	● C3688-05-00600	
6	1/4	600	2,000	1.70	● C3680-06-00600	● C3681-06-00600	● C3683-06-00600	● C3688-06-00600	

Cover: Polyester Core: Continuous filament



ONE-DESIGN

Endless Control

A control line with a special balanced cover-to-core fiber ratio is easily spliced into endless loops. The cover reduces stretch; the bright polyester fibers in the cover allow you to distinguish between the ropes onboard easily. It works perfectly for endless control lines on dinghies.



NEW!

FIND OUT MORE:



Ø mm	in	Length ft	BL Lbs.	Weight lbs/100	Color/Item no. blue/black	neon orange/black	red/black	neon yellow/black	Designed and best used as:
4	5/32	656	550	0.80	● 7156407	● 7156409	● 7156408	● 7156410	
5	3/16	656	6850	0.90	● 7156403	● 7156405	● 7156404	● 7156406	

Cover: Polyester /HMPE Core: Polyester



ONE-DESIGN

Bzzz Line

It's single braid construction makes Bzzz Line kink-free, while the unique combination of spun polyester and multi-filament polypropylene makes it soft on the hands and lightweight. Unlike other single braids that flatten out after time or squish in cleats, Bzzz Line retains its round shape allowing for better grip and ease of cleating. It also runs smoothly through blocks and stays soft use after use.



Ø mm	in	Length ft	BL Lbs.	Weight lbs/100	Color/Item no. green	blue	yellow	grey	Designed and best used as:
7	9/32	600	1,750	1.90	● C1692-07-00600	● C1693-07-00600			dinghy sheets, club boats
8	5/16	600	3,000	2.50			● C1696-08-00600	● C1698-08-00600	

Single Braid Polyester

PERFORMANCE BRAIDS



NEW ENGLAND ROPES® UNDERSTANDS
THAT EACH CONTROL LINE MUST MEET THE
PERFORMANCE DEMANDS OF ITS CLASS
AND WITHSTAND THE RIGORS OF HIGH-
PERFORMANCE SAILING, ENABLING SAILORS
TO REACH THEIR FULL POTENTIAL..



PERFORMANCE BRAID

Sta-Set®

Sta-Set® is the quintessential, proven-performance double braid. As the #1 double braid in America, Sta-Set® is strong, flexible, and long-wearing. It offers high strength, low stretch, and exceptional durability—yet remains soft and easy to handle over time. Splicing is simple, making it a favorite among sailors.

A true multi-purpose line, Sta-Set® is ideal for sheets and control lines on a wide range of boats, from dinghy's to keel boats. It's the perfect choice for collegiate programs and sailing schools seeking a high-quality, dependable line with superior durability.




Ø		Length	BL	Weight	Color/Item no.					Designed and best used
mm	in	mft	Lbs.	lbs/100	white w/tracer	red fleck	green fleck	blue fleck	black w/white fleck	as:
5	3/16	600	1,400	1.10	● 2100-06-00600	● 2111-06-00600	● 2112-06-00600	● 2113-06-00600	● 2104-06-00600	halyards, mainsheets, jib sheets, and control lines
6	1/4	600	2,350	2.00	● 2100-08-00600	● 2111-08-00600	● 2112-08-00600	● 2113-08-00600	● 2104-08-00600	
8	5/16	600	3,850	3.10	● 2100-10-00600	● 2111-10-00600	● 2112-10-00600	● 2113-10-00600	● 2104-10-00600	
10	3/8	600	5,100	4.30	○ 2100-12-00600	● 2111-12-00600	● 2112-12-00600	● 2113-12-00600	● 2104-12-00600	
11	7/16	600	7,000	6.00	● 2100-14-00600	● 2111-14-00600	● 2112-14-00600	● 2113-14-00600	● 2104-14-00600	
12	1/2	600	10,100	7.80	● 2100-16-00600	● 2111-16-00600	● 2112-16-00600	● 2113-16-00600	● 2104-16-00600	
14	9/16	600	11,700	10.10	● 2100-18-00600	● 2111-18-00600	● 2112-18-00600	● 2113-18-00600	● 2104-18-00600	
16	5/8	600	16,900	11.90	○ 2100-20-00600	● 2111-20-00600	● 2112-20-00600	● 2113-20-00600	● 2104-20-00600	
18	3/4	600	23,500	17.00	○ 2100-24-00600	● 2111-24-00600	● 2112-24-00600	● 2113-24-00600	● 2104-24-00600	

Cover: Polyester Core: Polyester



PERFORMANCE BRAID

Sta-Set® (Solid)



Ø		Length	BL	Weight	Color/Item no.					Designed and best used
mm	in	ft	Lbs.	lbs/100	white	red	green	blue	black	as:
5	3/16	600	1,400	1.10	● 2090-06-00600	● 2101-06-00600	● 2102-06-00600	● 2103-06-00600	● 2084-06-00600	halyards, mainsheets, jib sheets, and control lines
6	1/4	600	2,350	2.00	● 2090-08-00600	● 2101-08-00600	● 2102-08-00600	● 2103-08-00600	● 2084-08-00600	
8	5/16	600	3,850	3.10	● 2090-10-00600	● 2101-10-00600	● 2102-10-00600	● 2103-10-00600	● 2084-10-00600	
10	3/8	600	5,100	4.30	● 2090-12-00600	● 2101-12-00600	● 2102-12-00600	● 2103-12-00600	● 2084-12-00600	
11	7/16	600	7,000	6.00	● 2090-14-00600	● 2101-14-00600	● 2102-14-00600	● 2103-14-00600	● 2084-14-00600	
12	1/2	600	10,100	7.80	● 2090-16-00600	● 2101-16-00600	● 2102-16-00600	● 2103-16-00600	● 2084-16-00600	
14	9/16	600	11,700	10.10	● 2090-18-00600	● 2101-18-00600	● 2102-18-00600	● 2103-18-00600	● 2084-18-00600	
16	5/8	600	16,900	11.90	● 2090-20-00600	● 2101-20-00600	-	● 2103-20-00600	● 2084-20-00600	
18	3/4	600	23,500	17.00	● 2090-24-00600	● 2101-24-00600	● 2102-24-00600	● 2103-24-00600	● 2084-24-00600	

Cover: Polyeste Core: Polyester




PERFORMANCE BRAID

Vintage Sta-Set®

The #1 double braid in America is now available in a traditional classic shade! High strength, low stretch, extremely durable, Vintage Sta-Set® is made with 20% spun fiber and will remain soft over time.

Ø mm	in	Length ft	BL Lbs.	Weight lbs/100	Color/Item no. natural tan	Designed and best used as:
6	1/4	600	1,700	2.10	● C2650-08-00600	halyards, mainsheets, jib sheets, and control lines
8	5/16	600	2,700	3.50	● C2650-10-00600	
10	3/8	600	3,700	4.40	● C2650-12-00600	
11	7/16	600	5,600	6.10	● C2650-14-00600	
12	1/2	600	7,500	7.80	● C2650-16-00600	
16	5/8	600	10,400	11.40	● C2650-20-00600	

Cover: Polyester Core: Polyester



PERFORMANCE BRAID

Regatta Braid

Flexible and easy to handle, Regatta Braid is 12-strand single braid made from spun and filament polyester. This soft and supple line runs freely and does not kink.

Ø mm	in	Length ft	BL Lbs.	Weight g/m	Color/Item no. white	Designed and best used as:
6	1/4	600	2,550	2.20	● C1250-08-00600	performance oriented halyard, light mainsheet, or jib sheet
8	5/16	600	3,300	3.00	● C1250-10-00600	
10	3/8	600	4,800	4.00	● C1250-12-00600	
11	7/16	600	6,500	6.30	● C1250-14-00600	
12	1/2	600	8,000	7.00	● C1250-16-00600	
16	5/8	600	12,400	10.30	● C1250-20-00600	

Single Braid Polyester



NEW ENGLAND ROPE® IS A TRADEMARK
OF TEUFELBERGER®, A GLOBALLY ACTIVE
FAMILY-OWNED ENTERPRISE.



FIBER ROPE

INDUSTRIAL FIBER ROPES
LIFE SAFETY ROPES
PAPER CARRIER ROPES
TREECARE
YACHTING ROPES




WIRE ROPE

CABLEWAY ROPES
CRANE & INDUSTRIAL
ROPES
MINING ROPES
OFFSHORE ROPES
S&S / TECI
TENSOSTRUCTURES



STRAPPING SOLUTIONS

PET STRAPPING
PP STRAPPING
BETTER.COLLECT



One Company

INFINITE POSSIBILITIES

WHAT STARTED BACK IN 1790 AS A SIMPLE SHOP MAKING HEMP ROPES HAS SINCE EVOLVED INTO A GLOBALLY SUCCESSFUL GROUP OF ENTERPRISES SPECIALIZING IN THE DEVELOPMENT AND PRODUCTION OF FIBER AND STEEL WIRE ROPES AS WELL AS STRAPPING.

INNOVATIVE PRODUCTS OF OUTSTANDING QUALITY

Our expertise in a wide range of technologies has generated numerous synergies between our various divisions, much to the benefit of our customers. By assigning five percent of our employees to research and development, we make sure that our customers keep benefitting from cutting-edge technologies. In addition to upholding social and environmental standards, we also pay close attention to delivering consistently high quality and make sure that all our products comply with our quality standards. We work on an equal footing with our customers to find optimal solutions in the field of fiber ropes and their applications. The continuity and stability of our family business make us a reliable partner who can support you in solving your daily challenges.




QUALITY WITHOUT COMPROMISES

AT TEUFELBERGER®, QUALITY IS A KEY PRIORITY. FROM THE RECEIPT OF THE RAW MATERIALS TO THE DELIVERY OF THE FINISHED PRODUCT, STRICT QUALITY CHECKS ARE STANDARD PRACTICE.

YOUR TRUSTED PARTNER

Our portfolio is already extensive, nevertheless we continue to develop innovative products that meet your evolving needs and requirements. Teufelberger® offers comprehensive expertise in various segments of rope engineering, which gives you a decisive advantage in the selection and development of your rope.



14 LOCATIONS
AROUND THE WORLD
MANUFACTURING SITES
IN AUSTRIA, ITALY, POLAND,
THAILAND, THE CZECH
REPUBLIC, AND THE U.S.

GLOBAL NETWORK AND MARKET PROXIMITY

The keys to our success are international locations and a high degree of interaction with the customer. Our product development teams in Europe and the US work closely with our customers and external partners, like research institutes and certification authorities, to create products that do not only meet European and International standards but also live up to the high expectations of professionals.

PRODUCT DEVELOPMENT IS KEY

The development of our product portfolio is an ongoing process fueled by our innovative spirit, our aspirations for continuous improvement and our passion to develop the best products.

Our product development process incorporates fiber research and testing, prototype development, internal inspections, tests for compatibility with commercially available products, field tests and practical trials by experienced users.

DOCK AND ANCHOR LINES



WHETHER YOU'RE LEAVING YOUR BOAT
AT ANCHOR OR AT THE DOCK, IN ANY
WEATHER OR SEA STATE, OUR PREMIUM
DOCK AND ANCHOR LINES WORK 24/7 TO
KEEP IT SAFE AND SECURE



DOCK LINE

3-Strand Nylon

(larger sizes available, commercial marine)

Premium 3-Strand Nylon is a long-wearing, flexible and easy-to-handle rope that has greater strength and better abrasion resistance than all other 3-strand nylon lines. The highest tenacity nylon treated with our proprietary Marine Tech coating increases its wet strength and improves its fiber-to-fiber abrasion.



Ø		Length	BL	Weight	Color/Item no.			Designed and best used as:
mm	in				white	black	navy	
5	3/16	1200	1,300	0.90	● C7050-06-01200	● C7014-06-01200		dock, anchoring, and mooring lines
6	1/4	1200	2,100	1.60	● C7050-08-01200	● C7014-08-01200		
8	5/16	600	3,000	2.40	● C7050-10-00600	● C7014-10-00600		
10	3/8	600	4,250	3.50	○ C7050-12-00600	○ C7014-12-00600	○ C7013-12-00600	
11	7/16	600	6,000	4.60	● C7050-14-00600	● C7014-14-00600		
12	1/2	600	7,500	6.30	● C7050-16-00600	● C7014-16-00600	● C7013-16-00600	
14	9/16	600	8,800	8.00	● C7050-18-00600	● C7014-18-00600	● C7013-18-00600	
16	5/8	600	11,650	9.60	○ C7050-20-00600	○ C7014-20-00600	○ C7013-20-00600	
18	3/4	600	17,150	13.70	● C7050-24-00600	● C7014-24-00600	● C7013-24-00600	
22	7/8	600	22,300	18.70	● C7050-28-00600	● C7014-28-00600		
25	1	600	27,700	24.30	○ C7050-32-00600	○ C7014-32-00600		

Three Strand Nylon

“

Our **PREMIUM 3-STRAND NYLON ROPE** features outstanding strength and high abrasion resistance.

”





DOCK LINE

Double Braid Nylon

The perfect combination of high-grade marine nylon, special torque balanced construction, and a unique stabilization process produces this long wearing line that resists kinking. Double Braid Nylon has superb handling and the largest assortment of colors on the market. Available by the spool or in packaged, factory-spliced dock and anchor lines.



Ø		Length	BL	Weight	Color/Item no.				Designed and best used
mm	in	ft	Lbs.	lbs/100	white	white-gold	navy	hunter	as:
5	3/16	600	1,200	600	● C2010-06-00600	-	-	-	dock line
6	1/4	600	2,100	600	● C2010-08-00600	-	● C2053-08-00600	● C2052-08-00600	
8	5/16	600	2,900	600	● C2010-10-00600	-	-	-	
10	3/8	600	6,700	600	● C2010-12-00600	● C2059-12-00600	● C2053-12-00600	● C2052-12-00600	
11	7/16	600	8,000	600	● C2010-14-00600	● C2059-14-00600	-	-	
12	1/2	600	13,100	600	● C2010-16-00600	● C2059-16-00600	● C2053-16-00600	● C2052-16-00600	
16	5/8	600	20,500	600	● C2010-20-00600	● C2059-20-00600	● C2053-20-00600	● C2052-20-00600	
18	3/4	600	24,750	600	● C2010-24-00600	● C2059-24-00600	● C2053-24-00600	● C2052-24-00600	
22	7/8	600	32,750	600	● C2010-28-00600	-	● C2053-28-00600	● C2052-28-00600	
25	1	600	43,700	600	● C2010-32-00600	-	● C2053-32-00600	● C2052-32-00600	
28	1 1/8	600	47,700	600	● C2010-36-00600	-	● C2053-36-00600	● C2052-36-00600	
30	1 1/4	600	60,250	600	● C2010-40-00600	-	● C2053-40-00600	● C2052-40-00600	

Cover: Nylon Core: Nylon

Ø		Length	BL	Weight	Color/Item no.					Designed and best used
mm	in	ft	Lbs.	lbs/100	red	black	blue	teal	grey	as:
5	3/16	600	1,200	600	-	-	-	-	-	dock line
6	1/4	600	2,100	600	● C2011-08-00600	● C2014-08-00600	● C2013-08-00600	● C2017-08-00600	● C2058-08-00600	
8	5/16	600	2,900	600						
10	3/8	600	6,700	600	● C2011-12-00600	● C2014-12-00600	● C2013-12-00600	● C2017-12-00600	● C2058-12-00600	
11	7/16	600	8,000	600						
12	1/2	600	13,100	600	● C2011-16-00600	● C2014-16-00600	● C2013-16-00600	● C2017-16-00600	● C2058-16-00600	
16	5/8	600	20,500	600	● C2011-20-00600	● C2014-20-00600	● C2013-20-00600	● C2017-20-00600	● C2058-20-00600	
18	3/4	600	24,750	600	● C2011-24-00600	● C2014-24-00600	● C2013-24-00600	● C2017-24-00600	● C2058-24-00600	
22	7/8	600	32,750	600	● C2011-28-00600	● C2014-28-00600	● C2013-28-00600	● C2017-28-00600	● C2058-28-00600	
25	1	600	43,700	600	● C2011-32-00600	● C2014-32-00600	● C2013-32-00600	● C2017-32-00600	● C2058-32-00600	
28	1 1/8	600	60,250	600	● C2011-36-00600	● C2014-36-00600	● C2013-36-00600	● C2017-36-00600	● C2058-36-00600	
30	1 1/4	600			● C2011-40-00600	● C2014-40-00600	● C2013-40-00600	● C2017-40-00600	● C2058-40-00600	

Cover: Nylon Core: Nylon



DOCK LINE

ANCHOR LINE

Mega Braid

Mega Braid's unique 12-strand, single braid construction offers a combination of good looks, superb handling characteristics, excellent strength, and controlled elongation. It's flexible, easy to handle, resists kinking, and is both easy to coil and flake. Available in 600' spools or custom spliced.

Ø mm	in	Length ft	BL Lbs.	Weight lbs/100	Color/Item no. white	black	Designed and best used as:
16	5/8	600	10,300	9.9	● C1110-20-00600	● C1114-20-00600	dock line, mooring line
18	3/4	600	13,400	14.0	● C1110-24-00600	● C1114-24-00600	
22	7/8	600	21,100	17.2	● C1110-28-00600	● C1114-28-00600	
25	1	600	24,900	25.8	○ C1110-32-00600	○ C1114-32-00600	
28	1 1/8	600	34,900	34.0	● C1110-36-00600	● C1114-36-00600	
30	1 1/4	600	41,000	36.0	● C1110-40-00600	● C1114-40-00600	
36	1 1/2	600	48,000	55.50	○ C1110-50-00600	○ C1114-50-00600	

12 Strand Nylon



DOCK LINE


ANCHOR LINE

Mega Braid II

Mega Braid II is an abrasion resistant 12-strand nylon line. Each of its strands are individually braided resulting in an extremely firm yet flexible rope that resists picking and chafing. This line offers excellent abrasion resistance, is ideal for docking usage, and is easy to flake or coil.

Ø mm	in	Length ft	BL Lbs.	Weight lbs/100	Color/Item no. black	Designed and best used as:
12	9/16	600	6,500	6.20	● C1130-16-00600	dock line, anchor line
16	5/8	600	8,500	7.30	● C1130-20-00600	

12 Strand Nylon



DOCK LINE

ANCHOR LINE

Mega Plait

Mega Plait strikes a balance between a supple, firm, easy handling line that can be used in mechanical windlasses without abrading or fraying. Its unique tandem braid design results in a cube-shaped rope that functions well in mechanical windlasses. It will not abraid or become frayed as a result of its unique shape and is heat-set to increase its performance and durability when put into service.

Ø mm	in	Length ft	BL Lbs.	Weight lbs/100	Color/Item no. white	Designed and best used as:
16	1/2	600	9,500	8.30	● C1180-16-00600	anchor line, dock line, towing
18	9/16	600	11,000	9.30	● C1180-18-00600	
20	5/8	600	15,000	14.0	● C1180-20-00600	
24	3/4	600	15,000	14.0	● C1180-24-00600	

12 Strand Nylon



DOCK LINE

ANCHOR LINE

8-Plait

An anchor line specially designed for use in popular mechanical windlasses, Plait strikes a balance between a supple, firm, easy handling line that can be used in mechanical windlasses without abraiding or fraying. Engineered to work in most major windlass models and uniquely designed to be spliced to chain. Non kinking and non hocking unlike 3 strand, 8 plait stores easily in small spaces and has a higher elasticity and strength for stability in rough waters.

Ø		Length	BL	Weight	Color/Item no.	Designed and best used
mm	in	ft	Lbs.	lbs/100	white	as:
12	1/2	600	8,000	6.20	● C1340-16-00600	anchor line, dock line, fender line
12	1/2	3000	8,000	6.20	● C1340-16-03000B	
14	9/16	600	9,500	8.00	● C1340-18-00600	
14	9/16	3000	9,500	8.00	● C1340-18-03000B	
16	5/8	600	11,000	9.30	● C1340-20-00600	
16	5/8	1800	11,000	9.30	● C1340-20-03000B	
18	3/4	600	13,400	14.00	● C1340-24-00600	
18	3/4	1200	13,400	14.00	● C1340-24-03000B	
22	7/8	600	21,100	17.20	● C1340-28-00600	
22	7/8	1200	21,100	17.20	● C1340-28-03000B	


8 Strand Nylon



TOWING

Dinghy Tow Rope

Dinghy Tow Rope is a durable, brightly colored, spliceable tow line that floats on the surface of the water for improved visibility. This double braided rope of nylon over polypropylene is torque free and non hocking. It's braided design is easily spliced and easy to handle. Dinghy Tow Rope retains its strength when wet or dry.



Ø		Length	BL	Weight	Color/Item no.	Designed and best used
mm	in	ft	Lbs.	lbs/100	red fleck	as:
9.5	1/4	600	2,900	4.10	● C2381-12-00600	tow rope, floating safety line
11	3/8	600	5,050	5.30	● C2381-14-00600	

Cover: Nylon Core: Polypropylene



3 STRAND TRADITIONAL



NEW ENGLAND ROPES® TRADITIONAL
THREE STRAND ROPES PROVIDES THE
STRENGTH OF MODERN DAY TECHNOLOGY
WITH THE CLASSIC LOOK OF HEMP



3 STRAND

3-Strand Classic Polyester

A traditional low stretch running rigging, continuous filament 3-strand polyester rope, Classic provides excellent abrasion resistance with low stretch and high strength attributes. Easy to splice.



Ø		Length ft	BL Lbs.	Weight lbs/100	Color/Item no.		Designed and best used as:
mm	in				white	black	
5	3/16	600	1,090	1.07	● C7200-06-00600	● C7204-06-00600	genoa halyard, main halyard, traditional running rigging, luff line
6	1/4	600	2,150	1.98	● C7200-08-00600	● C7204-08-00600	
8	5/16	600	2,650	2.85	● C7200-10-00600	● C7204-10-00600	
10	3/8	600	4,400	4.75	○ C7200-12-00600	○ C7204-12-00600	
11	7/16	600	5,700	5.90	● C7200-14-00600	● C7204-14-00600	
12	1/2	600	7,500	7.90	● C7200-16-00600	● C7204-16-00600	
16	9/16	600	11,600	11.60	● C7200-20-00600	● C7204-20-00600	
18	5/8	600	14,650	15.90	● C7200-24-00600	● C7204-24-00600	
24	1	600	25,450	29.70	○ C7200-32-00600	○ C7204-32-00600	

3-Strand Braided Polyester



3 STRAND

Vintage 3-Strand

Low stretch running rigging available in a classic shade just perfect for the traditional vessel. Excellent abrasion resistance with low stretch and high strength. Easy to splice. A traditional look with today's performance

Ø		Length ft	BL Lbs.	Weight lbs/100	Color/Item no.		Designed and best used as:
mm	in				natural tan		
3	5/32	600	730	0.67	● C7000-04-00600		genoa halyard, main halyard, traditional running rigging, luff line
6	1/4	600	1,450	1.67	● C7000-08-00600		
8	5/16	600	2,100	2.61	● C7000-10-00600		
10	3/8	600	3,450	4.40	○ C7000-12-00600		
11	7/16	600	4,150	5.12	● C7000-14-00600		
12	1/2	600	6,200	7.30	● C7000-16-00600		
16	5/8	600	8,100	11.10	● C7000-20-00600		
18	3/4	600	12,400	15.00	○ C7000-24-00600		
24	1	600	20,200	28.75	○ C7000-32-00600		

3-Strand Braid Polyester



3 STRAND

Spun Classic Polyester

For a traditional look and feel, a conventional 3-strand spun polyester rope, Spun Classic is a soft, free running rope that resists jamming and kinking.

Ø		Length	BL	Weight	Color/Item no.	Designed and best used as:
mm	in	ft	Lbs.	lbs/100	soft white	
5	3/16	600	1,200	1.40	● C7230-05-01200	halyards, control lines, bolt rope
6	1/4	600	1,330	1.90	● C7230-06-01200	
8	5/16	600	2,000	2.70	● C7230-08-00600	
10	3/8	600	2,650	3.60	● C7230-10-00600	
11	7/16	600	3,250	4.80	● C7230-11-00600	
12	1/2	600	4,700	6.00	● C7230-12-00600	
16	5/8	600	6,700	10.10	● C7230-16-00600	

3-Strand Braided Polyester



3 STRAND

Spun Polypropylene

Spun polypropylene bridges the gap between modern cordage and traditional appearance. Extremely light fibers make spun polypropylene long-lasting, abrasion-resistant, low-stretch, and resistant to water absorption, it can be used for traditional rigging as well as for decorative purposes.

Ø	Length	BL	Weight	Color/Item no.	Designed and best used	
mm	in	ft	Lbs.	lbs/100	natural tan	as:
8	5/16	720	2,160	1.90	● 7157171	traditional rigging, decorative
10	3/8	720	3,215	3.00	● 7157172	
12	1/2	720	4,560	4.90	● 7157173	
14	9/16	720	6,275	6.30	● 7157180	
16	5/8	720	7,870	8.30	● 7157046	
18	3/4	720	10,120	9.50	● 7157047	
20	13/16	720	12,365	12.30	● 7157174	
22	7/8	720	15,065	14.70	● 7157175	
24	1	720	16,860	17.00	● 7157176	
28	1 1/8	720	22,700	23.20	● 7157048	
32	1 1/4	720			● 7157178	

3-Strand Braided Polypropylene



CORDS

3-Strand Polypropylene

Lightweight floating rope for non-critical low-load use: 3-strand polypropylene floats, has very little stretch, and is resistant to chemicals. Perfect for heaving lines, water-ski tow rope, life-ring lanyards, and quots. Water and mildew resistant. The 3-strand construction allows for simple splicing.

Ø		Length	BL	Weight	Color/Item no.	Designed and best used
mm	in					
5	3/16	1200	1,060	0.70	● 7905-06-01200	heaving lines, tow rope, life ring lanyards, quots, boundary markers, dinghy painters
6	1/4	1200	1,680	1.21	● 7905-08-01200	
8	5/16	600	2,250	2.06	● 7905-10-00600	
10	3/8	600	3,900	3.00	● 7905-12-00600	
11	7/16	600	4,650	3.90	● 7905-14-00600	
12	1/2	600	5,700	4.60	● 7905-16-00600	
16	5/8	600	8,200	7.30	● 7905-20-00600	
18	3/4	600	11,400	9.90	● 7905-24-00600	

3-Strand Braided Polypropylene



“

Sta-Set is the quintessential
proven performance double braid
and **THE #1 DOUBLE BRAID IN AMERICA!**

”





PACKAGED GOODS



DOCKING & ANCHORING

BOAT SIZE (Feet)	BOAT SIZE (Inch)	3-DRAWN TWISTED Lbs.	DOUBLE Braid TWISTED Lbs.
Up to 24'	3/8	4,250	4,800
25' - 34'	1/2	7,500	8,000
35' - 49'	5/8	11,650	13,100
50' - 65'	3/4	17,150	20,500
66' - 150'	1	19,500	23,200

Note: The breaking strength of dock ropes will be less than the listed values for white rope. 10% for 3-D Drawn and 5% for Double Braid.

Foot: 100 LBS DOCK LINE are usually 2/3 of the length of the boat.


SPRINK LINE: are usually equal to the length of the boat.

The position of the cleats on your boat may affect the length of the dock line.

The size, length, and type of line will depend on a number of factors including length, weight, and type of boat.

The following information is intended as a guide only.

Docking in exposed waters, strong winds, or tides may require larger or additional lines.







NEW ENGLAND ROPES® PRE-PACKAGED
DOCK AND ANCHOR LINES PROVIDE YOUR
CUSTOMERS WITH EASY COST EFFECTIVE
SOLUTIONS IN A VARIETY OF COLORS.

PACKAGED GOODS

Premium 3 Strand Docklines

Premium 3-Strand nylon dock lines are made utilizing a four-stage balanced construction with heat stabilization for a durable, long-lasting rope. This attention to detail produces a dock line that is easy to handle and will not harden with age. They are professionally hand spliced with five tucks, a whipped bitter end and a 12" eye.

We have introduced New 1 inch docklines for 2025 for use with larger yachts to provide the strength and stability these larger craft require at dock.



Ø	Ø	Length	BL	Weight	Color/Item no.			Designed and best used
mm	in	ft	Lbs.	lbs/100	white	navy	black	as:
10	3/8	10	4,250	3.50	● C6050-12-00010			dock line
10	3/8	15	4,250	3.50	● C6050-12-00015	● C6053-12-00015	● C6054-12-00015	
10	3/8	20	4,250	3.50	● C6050-12-00020		● C6054-12-00020	
10	3/8	25	4,250	3.50	● C6050-12-00025	● C6053-12-00025	● C6054-12-00025	
10	3/8	50	4,250	3.50	● C6050-12-00050			
12	1/2	15	7,500	6.30	● C6050-16-00015	● C6053-16-00015	● C6054-16-00015	
12	1/2	20	7,500	6.30	● C6050-16-00020			
12	1/2	25	7,500	6.30	● C6050-16-00025	● C6053-16-00025	● C6054-16-00025	
12	1/2	35	7,500	6.30	● C6050-16-00035	● C6053-16-00035	● C6054-16-00035	
12	1/2	50	7,500	6.30	● C6050-16-00050			
16	5/8	15	11,650	9.60	● C6050-20-00015	● C6053-20-00015	● C6054-20-00015	
16	5/8	25	11,650	9.60	● C6050-20-00025	● C6053-20-00025	● C6054-20-00025	
16	5/8	30	11,650	9.60	● C6050-20-00030			
16	5/8	35	4,250	3.50	● C6050-20-00035	● C6053-20-00035	● C6054-20-00035	
16	5/8	40	4,250	3.50	● C6050-20-00040		● C6054-20-00040	
16	5/8	50	4,250	3.50	● C6050-20-00050		● C6054-20-00050	
18	3/4	25	17,150	13.70	● C6050-24-00015			
18	3/4	35	17,150	13.70	● C6050-24-00025		● C6054-24-00025	
18	3/4	50	17,150	13.70	● C6050-24-00035		● C6054-24-00035	
18	3/4	50	17,150	13.70	● C6050-24-00050		● C6054-24-00050	
24	1	35	27,700	24.30	● C6050-32-00035		● C6054-32-00035	
24	1	50	27,700	24.30	● C6050-32-00050		● C6054-32-00050	

3-Strand Braided Nylon

PACKAGED GOODS

Premium Nylon Double Braid Docklines

Our Double Braid is the strongest and easiest-to-handle line you can buy that stays flexible throughout its service life. The core and cover are constructed from the highest quality treated nylon. The combination of high-grade marine nylon, special torque-balanced construction, and a unique stabilization process produces a long-wearing, easy-to-handle line that resists kinking. Our double braid lines offer controlled elongation and excellent abrasion resistance. Double braid lines stretch slightly less but are stronger than three strand lines. Each line has a professionally spliced 12" eye.

We have also introduced 1 new 1-inch docklines for 2025 for use with larger craft to provide them the safety and support these vessels need while at dock.

Ø		Length	BL	Weight	Color/Item no.					Designed and best used as:
mm	in	ft	Lbs.	lbs/100	white	white-gold	navy	hunter	red	
10	3/8	15	4,800	4.20	● 5050-12-00015	● 5059-12-00015	● 5063-12-00015	● 5062-12-00015	● 5051-12-00015	dock line
10	3/8	20	4,800	4.20	●	● 5059-12-00020	● 5063-12-00020	● 5062-12-00020	● 5051-12-00020	
12	1/2	25	8,000	7.00	● 5050-12-00025	● 5059-12-00025	● 5063-12-00025	● 5062-12-00025	● 5051-12-00025	
12	1/2	15	8,000	7.00	● 5050-16-00015	● 5059-16-00015	● 5063-16-00015	● 5062-16-00015	● 5051-16-00015	
12	1/2	25	8,000	7.00	● 5050-16-00025	● 5059-16-00025	● 5063-16-00025	● 5062-16-00025	● 5051-16-00025	
16	5/8	35	13,100	10.00	● 5050-16-00035	● 5059-16-00035	● 5063-16-00035	● 5062-16-00035	● 5051-16-00035	
16	5/8	15	13,100	10.00	● 5050-20-00015	● 5059-20-00015	● 5063-20-00015	● 5062-20-00015	● 5051-20-00015	
16	5/8	25	13,100	10.00	● 5050-20-00025	● 5059-20-00025	● 5063-20-00025	● 5062-20-00025	● 5051-20-00025	
16	5/8	35	13,100	10.00	● 5050-20-00035	● 5059-20-00035	● 5063-20-00035	● 5062-20-00035	● 5051-20-00035	
16	5/8	40	13,100	10.00	● 5050-20-00040	● 5059-20-00040	● 5063-20-00040	● 5062-20-00040	● 5051-20-00040	
18	3/4	50	20,500	15.00	● 5050-20-00050	● 5059-20-00050	● 5063-20-00050	● 5062-20-00050	● 5051-20-00050	
18	3/4	25	20,500	15.00	● 5050-20-00025	● 5059-24-00025	● 5063-24-00025	● 5062-24-00025	● 5051-24-00025	
18	3/4	35	20,500	15.00	● 5050-20-00035	● 5059-24-00035	● 5063-24-00035	● 5062-24-00035	● 5051-24-00035	
18	3/4	50	20,500	15.00	● 5050-20-00050	● 5059-24-00050	● 5063-24-00050	● 5062-24-00050	● 5051-24-00050	
24	1	35	29,200	24.40	● 57460-32-00035	● 57469-32-00035	● 57463-32-00035	-	-	
24	1	50	29,200	24.40	● 57460-32-00050	● 57469-32-00050	● 57463-32-00050	-	-	

Ø		Length	BL	Weight	Color/Item no.			Designed and best used as:
mm	in	ft	Lbs.	lbs/100	black	teal	grey	
10	3/8	15	4,800	4.20	● 5054-12-00015	● 5057-12-00015	● 5058-12-00015	dock line
10	3/8	20	4,800	4.20	● 5054-12-00020	● 5057-12-00020	● 5058-12-00020	
12	1/2	25	8,000	7.00	● 5054-12-00025	● 5057-12-00025	● 5058-12-00025	
12	1/2	15	8,000	7.00	● 5054-16-00015	● 5057-16-00015	● 5058-16-00015	
12	1/2	25	8,000	7.00	● 5054-16-00025	● 5057-16-00025	● 5058-16-00025	
16	5/8	35	13,100	10.00	● 5054-16-00035	● 5057-16-00035	● 5058-16-00035	
16	5/8	15	13,100	10.00	● 5054-20-00015	● 5057-20-00015	● 5058-20-00015	
16	5/8	25	13,100	10.00	● 5054-20-00025	● 5057-20-00025	● 5058-20-00025	
16	5/8	35	13,100	10.00	● 5054-20-00035	● 5057-20-00035	● 5058-20-00035	
16	5/8	40	13,100	10.00	● 5054-20-00040	● 5057-20-00040	● 5058-20-00040	
18	3/4	50	20,500	15.00	● 5054-20-00050	● 5057-20-00050	● 5058-20-00050	
18	3/4	25	20,500	15.00	● 5054-24-00025	● 5057-24-00025	● 5058-24-00025	
18	3/4	35	20,500	15.00	● 5054-24-00035	● 5057-24-00035	● 5058-24-00035	
18	3/4	50	20,500	15.00	● 5054-24-00050	● 5057-24-00050	● 5058-24-00050	
24	1	35	29,200	24.40	● 57464-32-0035			
24	1	50	29,200	24.40	● 57464-32-0050			

Cover: Nylon Core: Nylon



PACKAGED GOODS

Nylon Fender Whips

Holds fenders with premium 3 Strand nylon rope with a spliced eye for tidy and easy fender deployment

Ø mm	in	Length ft	BL Lbs.	Weight lbs/100	Color/Item no. white	Designed and best used as:
10	3/8	6	4,250	3.50	● C8170-12-00006	fender whip
10	3/8	12	4,250	3.50	● C8170-12-00012	
12	1/2	6	7,500	6.30	● C8170-16-00006	
12	1/2	12	7,500	6.30	● C8170-16-00012	

3-Strand Braided Nylon



PACKAGED GOODS


ANCHORING/MOORING

Poly/Nylon Double Braid Mooring Pendant with Stainless Thimble

Poly/Nylon mooring pendants combine the strength and elasticity of nylon in the core with tough, durable abrasion resistant polyester in the cover. Poly/Nylon mooring pendants come standard with a thick yellow-tinted marine-tech coating that improves abrasion resistance and enhances visibility. Each pendant has a factory-spliced heavy duty galvanized thimble on the buoy end and a professionally spliced soft eye on the boat end. Poly/Nylon mooring pendants have a durable Cordura® chafe sleeve.

Ø mm	in	Length ft	BL Lbs.	Weight lbs/100	Eye in	poly-nylon	Designed and best used as:
16	5/8	12	15,000	11.0	12	● C538K6-20-00012	mooring pendant
16	5/8	15	15,000	11.0	15	● C538K6-24-00015	
18	3/4	12	20,900	16.0	15	● C538K6-24-00012	
18	3/4	15	20,900	16.0	15	● C538K6-24-00015	
18	3/4	20	20,900	16.0	15	● C538K6-24-00020	
24	1	20	35,430	31.0	24	● C539K6-32-00020	

Polyester/Nylon



PACKAGED GOODS

ANCHORING/MOORING

Cyclone Mooring Pendant

The ultimate in mooring pendants, made from out Endura 12® rope, Cyclone Mooring Pendants are comprised of Dyneema® fiber which has extremely high tensile strength and ultra low elongation. The Cyclone Mooring Pendant floats, has an excellent strength-to-size ratio, excellent wet/dry retention, and has a marine-tech coating which improves abrasion resistance. The Cyclone Mooring Pendant is used in conjunction with a traditional mooring pendant making it the ultimate in storm pendants.

Ø mm	in	Length ft	BL Lbs.	Weight lbs/100	Eye in	Color/Item no. poly-nylon	Designed and best used as:
12	1/2	6	34,300		10	● C54T93-16-00006	mooring pendant
12	1/2	8	34,300		10	● C54T93-16-00008	
16	5/8	5	58,000		10	● C54T93-20-00005	
18	3/4	6	67,000		12	● C54T93-24-00005	
18	3/4	8	67,000		12	● C54T93-24-00005	
18	3/4	12	67,000		18	● C54T93-24-00005	
22	7/8	12	97,500		24	● C54T93-28-00005	
24	1	12	114,000		24	● C54T03-32-00008	

Dyneema®



PACKAGED GOODS

ANCHORING/MOORING

3-Strand Mooring Pendant

3-strand mooring pendants are manufactured from our Premium 3-Strand Nylon line. Each pendant has a professional factory-spliced heavy duty galvanized thimble on the buoy end and a 12" soft eye on the boat end. Optional Cordura® chafe sleeve may be applied to enhance abrasion resistance. New England Ropes recommends the use of a swivel placed at the buoy to help eliminate twisting of the rope which can cause hockels or the rope to fall out of lay.

Ø mm	in	Length ft	BL Lbs.	Weight lbs/100	Eye in	Color/Item no. poly-nylon	3-strand	Designed and best used as:
16	5/8	12	15,000	11.10	12	● C539K6-20-00012	● C629K0-20-00012	mooring pendant
16	5/8	15	15,000	11.10	12	● C539K6-20-00015	● C629K0-20-00015	
18	3/4	15	20,900	15.90	15	● C539K6-24-00012	● C629K0-24-00012	
18	3/4	15	20,900	15.90	15	● C539K6-24-00015	● C629K0-24-00015	
18	3/4	20	20,900	15.90	15	● C539K6-24-00020	● C629K0-24-00020	
24	1	20	27,700	11.10	20		● C629K0-32-00020	
32	1 1/4				24	● C539K6-32-00020		

3-Strand Braided Nylon



PACKAGED GOODS

ANCHORING/MOORING

Nylon Anchor Line

Premium Three-Strand Nylon lines are designed to handle the dynamic shock loads caused by boat motion and are treated for maximum abrasion-resistance. New England Ropes® anchor lines are made of high-quality premium nylon using a uniform construction process and a marine coating that creates an extremely abrasion-resistant, snag-resistant and long-lasting line. Each anchor line is factory eye-spliced with a high-quality stainless steel thimble at one end and a heat-sealed bitter end. We package a variety of sizes and lengths to accommodate all your anchoring needs.

Ø mm	in	Length ft	BL Lbs.	Weight lbs/100	Color/Item no. white	Designed and best used as:
10	3/8	100	4,250	3.50	● C6060-12-00100	anchor line
10	3/8	150	4,250	3.50	● C6060-12-00150	
10	3/8	200	4,250	3.50	● C6060-12-00200	
12	1/2	100	7,500	6.30	● C6060-16-00100	
12	1/2	150	7,500	6.30	● C6060-16-00150	
12	1/2	200	7,500	6.30	● C6060-16-00200	
12	1/2	250	7,500	6.30	● C6060-16-00250	
12	1/2	300	7,500	6.30	● C6060-16-00300	
16	5/8	200	11,650	9.60	● C6060-20-00200	
16	5/8	250	11,650	9.60	● C6060-20-00250	
16	5/8	300	11,650	9.60	● C6060-20-00300	
18	3/4	250	17,150	13.70	● C6060-24-00250	
18	3/4	300	17,150	13.70	● C6060-24-00250	

3-Strand Braided Nylon



PACKAGED GOODS

ANCHORING/MOORING

Rope to Chain Anchor Rodes

New England Ropes® anchor lines are made of high-quality premium nylon using a uniform construction process and a marine coating that creates an extremely abrasion-resistant, snag-resistant and long-lasting line. Each anchor line is factory eye-spliced with a high-quality stainless steel thimble at one end and a heat-sealed bitter end.

Ø mm	in	Length ft	BL Lbs.	Weight lbs/100	Chain Dia. in	poly-nylon	Designed and best used for:
12	1/2	12	5000	45	1/4	● C62H20-16-00200	anchoring
12	1/2	15	8200	72	1/4	● C62H20-16-00250	
14	9/16	15	13900	101	5/16	● C62H30-18-00150	
14	9/16	15			5/16	● C62H40-18-00200	

3-Strand Braided Nylon



PACKAGED GOODS

ANCHORING/MOORING

Mega Plait Anchor Rodes

Mega Plait line is designed to handle use in popular mechanical windlasses without abrading or fraying. It's made of high-quality premium nylon. Supple, and easy handling, it flakes or coils tighter and uses less space than traditional three-strand nylon rodes, taking up less space in your anchor locker.

Ø mm	in	Length ft	BL Lbs.	Weight lbs/100	Color/Item no. white	Designed and best used for:
12	1/2	150	8,000	6.20	● 5070-16-00150	anchoring
12	1/2	250	8,000	6.20	● 5070-16-00250	
16	5/8	150	11,000	9.30	● 5070-20-00150	
16	5/8	250	11,000	9.30	● 5070-20-00250	

12-Strand Braided Nylon




PACKAGED GOODS

ANCHORING/MOORING

Mega Plait to Chain Anchor Rodes

Ø mm	in	Length ft	BL Lbs.	Weight lbs/100	Color/Item no. white	chain	Designed and best used for:
12	1/2	250	8,000	6.20	● 50H80-16-00250	● 1/4 x 20 ft chain length	anchoring
16	5/8	250	11,000	9.30	● 50H40-20-00250	● 5/16 x 20 ft chain length	

12-Strand Braided Nylon



HOOK N MOOR

Hook & Moor

This boat hook is extremely easy to use and brings your mooring rope through the ring and back onto the boat in one motion. Just a simple push or pull motion with the hook and it's done. No messenger line needed. The boat hook's adaptable length makes it easy to operate and store. Stay safe onboard when mooring and docking. It also works as a regular boat hook when the hook head is in locked position.

NEW!

FIND OUT MORE:



Item	Item no.
1.8 Meter (6 ft) Telescopic	● 7080217
2.5 Meter (8 ft) Telescopic	● 7080218
3.2 Meter (10.5 ft) Telescopic	● 7080219
4.2 Meter (13.8 ft) Telescopic	● 7080223
Mounting Clip	● 70889808
Replacement Head	● 7080220
Old Model Replacement Head	● 70889806




ACCESSORIES

Soft Shackles

Our lightweight and durable soft shackles are available in both Dyneema and HMPE constructions. Perfect for attaching sheets, mooring lines, and fender whips, they're easy to install and ready to use straight out of the box.

Ø		Length	BL	Weight	Color/Item no.		Designed and best used
mm	in	ft	Lbs.	g/m	black [Dyneema]	black [HMPE]	for:
3.5						● 7156460	soft shackle
4	5/32				● 7150547	● 7156461	
6	1/4				● 7150548	● 7156462	
9	3/8				● 7150549	● 7156463	
12	1/2				● 7150551	● 7156465	
14	9/16				● 7150546		

Dyneema® or HMPE



ACCESSORIES


Whipping Twine

Our waxed whipping twine is made of colored polyester and is particularly easy to handle and impresses users with the high quality of twisted PES twine. 262 feet per spoolette.

Ø		Case	Color/Item no.							Designed and best used
mm	in	Pack	black	blue	green	red	assorted	white		for:
0.5		10						● 7150539		whipping twine Dyneema® twine comes with sail maker needle
0.8		10	● 7150533	● 7150534	● 7150535	● 7150537	● 7150536	● 7150540		
0.8		10						● 7150544 [Dyneema®]		
1.0		10						● 7150545 [Dyneema®]		
1.0		10						● 7150541		
1.5		10						● 7150538		

Waxed Polyester Twine or Dyneema®

CORDS AND ACCESSORIES



FROM MESSENGER LINES TO RUN YOUR
HALYARDS THROUGH THE MAST TO HIGH
TECH SHOCK CORDS TO KEEP ITEMS
SECURE, WE HAVE THE SOLUTIONS YOU
NEED ABOVE AND BELOW DECK.



CORDS/ACCESSORIES


Braided Polyester Cord

Lightly braided polyester line. Ideal for general purpose use such as flag halyards and tiedowns.

white
black

Ø		Length	BL	Weight	Color/Item no.		Designed and best used
mm	in	ft	Lbs.	lbs/100	white	black	as:
2	3/32	2100	450	0.32	● 3500-02-01200		general purpose line for flag halyards, and tie downs
3	1/8	2100	580	0.46	● 3500-03-02100	● 3504-03-02100	
4	5/32	1200	790	0.73	● 3500-05-01200	● 3504-05-01200	
4	5/32	50	790	0.73	● 3500-05-00050		
5	3/16	1000	1,140	0.99	● 3500-06-01000	● 3504-05-01000	

Single Braid Polyester




CORDS

T-100

Strong, low-stretch, durable cord. 100% Technora® fiber core and a braided polyester cover. Very low stretch.

Ø	Length	BL	Weight	Color/Item no.	Designed and best used	
mm	in	Lbs.	lbs/100	white w/tracer		
2	3/32	1500	1,050	0.35	● C2580-03-01500	main sheets, jib sheets, and areas where you experience a bit more chafe than usual
3	1/8	1200	2,000	0.60	● C2580-04-01200	
4	5/32	900	2,900	0.93	● C2580-05-00900	
5	3/16	600	3,100	1.23	● C2580-06-00600	
6	1/4	600	5,050	1.90	● C2580-08-00600	

Cover: Polyester Core: Technora®



CORDS

Halyard Leader Line

Small tight double braid line that is great for all those times you need a quick utility line as a tie down or as a messenger line for running new halyards. When tensioned the line will "stand up" to make running lines or wires easier.

Ø	Length	BL	Weight	Color/Item no.					Designed and best used
mm	in	ft	Lbs.	lbs/100	red-white	green-white	blue-white	black-white	as:
2	3/32	12	460	0.32	● C3491-03-02100	● C3492-03-02100	● C3493-03-02100	● C3494-03-02100	messenger line, tie downs

Cover: Polyester/Technora®




CORDS

Braided Polyester Luffline

Stiff, durable, and strong. 100% Braided polyester has internal market strands to identify luffline by size.

Ø mm	in	Length ft	BL Lbs.	Weight lbs/100	Color/Item no. white-yellow	Designed and best used as:
3	1/8	1,800	370	0.47	● 3600-04-01800	luffline
4	5/32	1,200	750	0.81	● 3600-05-01200	
5	3/16	2,100	1,050	1.19	● 3600-06-2100	
5.5		1,200	1,275	1.76	● 3600-07-01200	
6	1/4	1,800	1,500	2.20	● 3600-08-01800	
7	9/32	1,500	1,800	2.40	● 3600-09-01500	


Single Braid Polyester



CORDS


Shock Cord

Top quality rubber is used in our shock cord which makes it compact, stable and durable. The outer cover is made of extremely abrasion resistant polyester



Ø mm	in	Length ft	BL Lbs.	Weight lbs/100	Color/Item no. white	white-red	black	blue	Designed and best used as:
3	1/8			1.90	● 7157738	● 7150978	● 7150979	-	retaining lines, tie downs
4	5/32			2.70	● 7157739	-	● 7159082	-	
5	3/16			3.10	● 7155159	● 7150931	● 7150934	● 7150932	
6	1/4			4.10	● 7155160	● 7150935	● 7150938	● 7150936	
8	5/16			7.10	● 7155161	● 7150939	● 7159084	-	
10	3/8			11.90	○ 7155162	● 7150928	● 7159085	-	


Cover: Polyester Core: Rubber



CORDS

NEW! High Tech Shock Cord

We have improved our shock cord with a HMPE cover over a quality rubber core. Elongation of 100% while maintaining a high breaking load. Low friction cover reduces wear and tear. Less wear on non-skid surfaces.



FIND OUT MORE:



NEW!

Ø mm	in	Length ft	BL Lbs.	Weight lbs/100	Color/Item no. white	black	Designed and best used for:
3	1/8	100	44	6.00	● 7156398	● 7156397	cascade systems
4	5/32	100	89	13.00	● 7156400	● 7156399	
5	3/16	100	97	17.00	● 7156402	● 7156401	
6	1/4	100	105	26.00	● 7156396	● 7156395	

Cover: Blended HMPE Core: Rubber



ACCESSORIES


Accessories

New England Ropes® in collaboration with riggers and a leading manufacturer of precision machined parts designed a unique, patented new fid kit for use on all types of ropes.

Item	Item no.
Uni-Fid II	● C9100-00-00000
Electric Rope Cutter	● C9010-00-00000
Rope Hanker	● C9040-00-00000
Cutter Replacement Blade	● C9020-00-00000
Cordage Meter [in Feet]	● C9030-00-00000
Cordage Meter [in Meters]	● C9031-00-00000
Cordage Meter Mount	● C9032-00-00000
5 Piece Selma Fid Kit	● C9240-00-00000
#4 (1/8 Circ.) Selma Fid	● C9241-00-00000
#5.5 (1/4 Circ.) Selma Fid	● C9242-00-00000
#7.5 (5/16 Circ.) Selma Fid	● C9243-00-00000
#10 (3/8 Circ.) Selma Fid	● C9244-00-00000
#20 (3/4 Circ.) Selma Fid	● C9246-00-00000
Tow Fid	● C9200-00-00000



COMMERCIAL MARINE



OUR COMMERCIAL MARINE PRODUCT LINE IS SPECIFICALLY ENGINEERED TO PROVIDE THE STRENGTH, ABRASION RESISTANCE, AND ELONGATION CHARACTERISTICS NECESSARY FOR THE MAJORITY OF COMMERCIAL MARINE OPERATIONS.




COMMERCIAL

Holdfast

This ropes utilizes HMPE and Nylon fibers to deliver a lightweight, high-strength, floating line that will grip on H-bitts and capstans much better than traditional 100% HMPE lines. Holdfast is coated with TEUFELBERGER's® proprietary abrasion resistant coating that is specially formulated to yield higher strength better grip and more durable and water-resistant lines. Holdfast is available in a variety of colors.

Ø mm	in	Length ft	BL Lbs.	Weight lbs/100	Color/Item no. blue	yellow	gray	red	Designed and best used as:
18	¾	600	38,900	14.76	C1833-24-00600	C1836-24-00600	C1838-24-00600	C1831-24-00600	mooring lines, winching lines, tug tow lines, and general purpose working line
22	7/8	600	49,700	18.05	C1833-24-00600	C1836-24-00600	C1838-24-00600	C1831-24-00600	
24	1	600	62,000	21.62	C1833-32-00600	C1836-32-00600	C1838-32-00600	C1831-32-00600	
28	1 1/8	600	77,500	30.93	C1833-36-00600	C1836-36-00600	C1838-36-00600	C1831-36-00600	
30	1 ¼	600	87,800	33.84	C1833-40-00600	C1836-40-00600	C1838-40-00600	C1831-40-00600	
32	1 5/16	600	102,500	38.54	C1833-24-00600	C1836-24-00600	C1838-24-00600	C1831-24-00600	
34	1 3/8	600	108,500	43.43	C1833-24-00600	C1836-24-00600	C1838-24-00600	C1831-24-00600	
36	1 ½	600	122,300	46.91	C1833-24-00600	C1836-24-00600	C1838-24-00600	C1831-24-00600	
40	1 5/8	600	146,000	58.84	C1833-24-00600	C1836-24-00600	C1838-24-00600	C1831-24-00600	
44	1 ¾	600	169,500	66.65	C1833-24-00600	C1836-24-00600	C1838-24-00600	C1831-24-00600	
48	2	600	196,500	79.15	C1833-56-00600	C1836-56-00600	C1838-56-00600	C1831-56-00600	
56	2 ¼	600	275,500	113.27	C1833-24-00600	C1836-24-00600	C1838-24-00600	C1831-24-00600	
60	2 ½	600	309,000	133.39	C1833-24-00600	C1836-24-00600	C1838-24-00600	C1831-24-00600	
64	2 5/8	600	362,000	160.93	C1833-24-00600	C1836-24-00600	C1838-24-00600	C1831-24-00600	
72	3	600	464,000	210.84	C1833-24-00600	C1836-24-00600	C1838-24-00600	C1831-24-00600	
Ø mm	in	Length ft	BL Lbs.	Weight lbs/100	Color/Item no. white	orange	neon green		Designed and best used as:
18	¾	600	38,900	14.76	C1830-24-00600	C1835-24-00600	C1832-24-00600		mooring lines, winching lines, tug tow lines, and general purpose working line
22	7/8	600	49,700	18.05	C1830-24-00600	C1835-24-00600	C1832-24-00600		
24	1	600	62,000	21.62	C1830-32-00600	C1835-32-00600	C1832-32-00600		
28	1 1/8	600	77,500	30.93	C1830-36-00600	C1835-36-00600	C1832-36-00600		
30	1 ¼	600	87,800	33.84	C1830-40-00600	C1835-40-00600	C1832-40-00600		
32	1 5/16	600	102,500	38.54	C1830-24-00600	C1835-24-00600	C1832-24-00600		
34	1 3/8	600	108,500	43.43	C1830-24-00600	C1835-24-00600	C1832-24-00600		
36	1 ½	600	122,300	46.91	C1830-24-00600	C1835-24-00600	C1832-24-00600		
40	1 5/8	600	146,000	58.84	C1830-24-00600	C1835-24-00600	C1832-24-00600		
44	1 ¾	600	169,500	66.65	C1830-24-00600	C1835-24-00600	C1832-24-00600		
48	2	600	196,500	79.15	C1830-56-00600	C1835-56-00600	C1832-56-00600		
56	2 ¼	600	275,500	113.27	C1830-24-00600	C1835-24-00600	C1832-24-00600		
60	2 ½	600	309,000	133.39	C1830-24-00600	C1835-24-00600	C1832-24-00600		
64	2 5/8	600	362,000	160.93	C1830-24-00600	C1835-24-00600	C1832-24-00600		
72	3	600	464,000	210.84	C1830-24-00600	C1835-24-00600	C1832-24-00600		

Single Braid HMPE and Nylon



COMMERCIAL

Endura-12®

Endura 12®, is a 12-strand single braid of 100% HMPE fiber for a light weight, low stretch, torque-free rope. Endura 12® is treated with our unique coating for improved abrasion and snag resistance.



Ø mm	in	Length ft	BL Lbs.	Weight lbs/100	Color/Item no. white	red	green	blue	Designed and best used as:
40	1 5/8	600	283,000	64.40	C1520-52-00600	C1521-52-00600	C1522-52-00600	C1523-52-00600	steel cable replacement, tug boat tow lines, tug pendant and main line, winch line, slings trawl line, wire rope replacement.
44	1 3/4	600	335,000	70.00	C1520-54-00600	C1521-54-00600	C1522-54-00600	C1523-54-00600	
48	2	600	381,000	82.20	C1520-56-00600	C1521-56-00600	C1522-56-00600	C1523-56-00600	
56	2 1/4	600	537,000	114.50	C1520-60-00600	C1521-60-00600	C1522-60-00600	C1523-60-00600	
60	2 1/2	600	588,000	128.60	C1520-62-00600	C1521-62-00600	C1522-62-00600	C1523-62-00600	
64	2 5/8	600	675,000	153.40	C1520-64-00600	C1521-64-00600	C1522-64-00600	C1523-64-00600	
72	3	600	856,000	189.30	C1520-68-00600	C1521-68-00600	C1522-68-00600	C1523-68-00600	
Ø mm	in	Length ft	BL Lbs.	Weight lbs/100	black	orange	yellow	gray	Designed and best used as:
40	1 5/8	600	283,000	64.40	C1524-52-00600	C1525-52-00600	C1526-52-00600	C1528-52-00600	steel cable replacement, tug boat tow lines, tug pendant and main line, winch line, slings trawl line, wire rope replacement.
44	1 3/4	600	335,000	70.00	C1524-54-00600	C1525-54-00600	C1526-54-00600	C1528-54-00600	
48	2	600	381,000	82.20	C1524-56-00600	C1525-56-00600	C1526-56-00600	C1528-56-00600	
56	2 1/4	600	537,000	114.50	C1524-60-00600	C1525-60-00600	C1526-60-00600	C1528-60-00600	
60	2 1/2	600	588,000	128.60	C1524-62-00600	C1525-62-00600	C1526-62-00600	C1528-62-00600	
64	2 5/8	600	675,000	153.40	C1524-64-00600	C1525-64-00600	C1526-64-00600	C1528-64-00600	
72	3	600	856,000	189.30	C1524-68-00600	C1525-68-00600	C1526-68-00600	C1528-68-00600	

Single Braid SK-75



COMMERCIAL

Endura Braid®

Endura Braid® is a line that provides optimal performance, strength, and durability. Featuring a specially engineered 12-strand Dyneema® coated core with a braided polyester cover, it protects against UV deterioration and wear. Endura Braid has good knot-tying ability and is very low stretch. colored polyester and is particularly easy to handle and impresses users with the high quality of twisted PES twine.

Ø mm	in	Length ft	BL Lbs.	Weight lbs/100	Color/Item no. white w/red and black tracer	Designed and best used as:
16	5/8	600	29,000	11.80	● C2530-16-00600	winch lines, tow lines, lifting lines, wire rope replacement
18	3/4	600	40,000	15.80	● C2530-24-00600	
22	7/8	600	53,900	20.90	● C2530-28-00600	
24	1	600	70,000	27.10	● C2530-32-00600	
28	1 1/8	600	96,000	34.40	● C2530-36-00600	

Cover: Polyester Core: Dyneema®



COMMERCIAL

Nylon Double Braid

Nylon Double Braid has the most elastic double braid construction available. It has excellent energy absorption properties and minimal strength loss due to UV exposure. It conforms to military specification Mil-R-24050 B&C and with twice as much stretch as polyester. Nylon Double Braid is great for docking and mooring lines because of its ability to absorb energy.

Ø mm	in	Length ft	BL Lbs.	Weight lbs/100	Color/Item no. white	Designed and best used as:
30	1 ¼	600	60,250	41.00	● C2010-40-00600	dock line, mooring, hand lines, pulling lines, slings, pendant lines
36	1 ½	600	77,550	55.70	● C2010-50-00600	
40	1 ⅝	600	99,000	69.40	● C2010-52-00600	
42	1 ¾	600	102,000	80.80	● C2010-54-00600	
48	2	600	131,000	100.50	● C2010-56-00600	

Cover: Nylon Core: Nylon



COMMERCIAL

Sta-Set®

Sta-Set® is a low-stretch durable double braid line ideal for all applications requiring control, positioning, lifting, or lowering lines. Sta-Set® has approximately 50% less stretch than the same construction in nylon.

Ø mm	in	Length ft	BL Lbs.	Weight lbs/100	Color/Item no. white w/red tracer	Designed and best used as:
12	½	600	10,100	7.80	● C2100-16-00600	utility line, lifting and lowering lines
14	⅞	600	11,700	10.10	● C2100-18-00600	
16	⅝	600	16,900	11.90	● C2100-20-00600	
18	¾	600	23,500	17.00	● C2100-24-00600	
22	⅞	600	33,800	23.70	● C2100-28-00600	
24	1	600	40,900	32.40	● C2100-32-00600	
28	1 ⅛	600	45,000	39.80	● C2100-36-00600	
30	1 ¼	600	54,750	49.20	● C2100-40-00600	

Cover: Polyester Core: Polyester



COMMERCIAL

Poly/Nylon Double Braid

A unique balanced construction consisting of a nylon core to provide stretch and a polyester cover for enhanced toughness and durability. Abrasion resistant.

Ø mm	Ø in	Length ft	BL Lbs.	Weight lbs/100	Color/Item no. white w/red flecks	Designed and best used as:
16	5/8	600	15,000	11.10	● C2300-20-00600	dock line, hand line, pulling line, pendant line
18	3/4	600	20,900	15.90	● C2300-24-00600	
22	7/8	600	30,980	22.60	● C2300-28-00600	
25	1	600	35,340	30.50	● C2300-32-00600	
28	1 1/8	600	53,250	37.50	● C2300-36-00600	

Cover: Polyester Core: Nylon



COMMERCIAL

HyperTEN

Hyperten lines are made using Stronger Than Steel® technology which is our patented process of adding heat and applying tension which aligns the rope fibers resulting in higher rope strength. As a result, Hyperten lines have a higher breaking strength, weigh less, have lower levels of stretch, and have a more stable cross-section than its non-heat set counterparts. This allows for smaller diameter lines to address applications typically requiring.

Ø mm	Ø in	Length ft	BL Lbs.	Weight lbs/100	Color/Item no. silver	Designed and best used as:
12	1/2	660	43,675	6.80	● C1628-12-00660	wire replacement, winches,
14	9/16	660	55,770	9.30	● C1628-14-00660	
16	5/8	660	65,950	11.00	● C1628-16-00660	
18	3/4	660	86,350	13.00	● C1628-18-00660	
20	13/16	660	103,650	17.70	● C1628-20-00660	
22	7/8	660	112,760	18.90	● C1628-22-00660	
24	1	660	130,900	23.30	● C1628-24-00660	

Single Braid HMPE



COMMERCIAL

Multiline II

Multiline II is a 3-strand composite line of which is comprised of three different fibers: polyolefin, filament polyester, and spun polyester. This unique combination of fibers creates a line that is lightweight, high strength, and has excellent grip and handling. The rope's excellent grip, handling, and knotability capabilities remain in tact even when the rope is wet. Easily spliceable. Abrasion resistant.

Ø mm	Ø in	Length ft	BL Lbs.	Weight lbs/100	Color/Item no. white w orange fleck	Designed and best used as:
8	5/16	600	2,060	2.66	● C7300-10-00600	scaffolding, pack rope, construction,
10	3/8	600	3,500	4.20	● C7300-12-00600	
10	3/8	1200	3,500	4.20	● C7300-12-01200	
11	7/16	600	4,300	5.20	● C7300-14-00600	
12	1/2	150	6,700	6.70	● C7300-16-00150	
12	1/2	600	6,700	6.70	● C7300-16-00600	
12	1/2	1200	6,700	6.70	● C7300-16-01200	
16	5/8	150	9,800	10.40	● C7300-20-00150	
16	5/8	600	9,800	10.40	● C7300-20-00600	
16	5/8	1200	9,800	10.40	● C7300-20-01200	
18	3/4	150	13,300	14.50	● C7300-24-00150	
18	3/4	600	13,300	14.50	● C7300-24-00600	
18	3/4	1200	13,300	14.50	● C7300-24-01200	
22	7/8	150	15,200	17.90	● C7300-28-00150	
22	7/8	600	15,200	17.90	● C7300-28-00600	
22	7/8	1200	15,200	17.90	● C7300-28-01200	
24	1	150	19,100	21.10	● C7300-32-00150	
24	1	600	19,100	21.10	● C7300-32-00600	
24	1	1200	19,100	21.10	● C7300-32-01200	

Single Braid Polyester, Polyolefin, Filament Polyester, Spun Polyester



COMMERCIAL

Mega Braid II

Mega Braid II is an abrasion resistant 12-strand nylon line. Each of its strands are individually braided resulting in an extremely firm yet flexible rope that resists picking and chafing. This line offers excellent abrasion resistance, is ideal for docking usage, and is easy to flake or coil.

Ø mm	Ø in	Length ft	BL Lbs.	Weight lbs/100	Color/Item no. white	black	Designed and best used as:
12	1/2	600	6,500	6.20	● C1130-16-00600	● C1134-16-00600	dock line, anchoring, trawl, bridle lines, general work line
14	9/16	600	8,500	7.30	● C1130-18-00600	● C1134-18-00600	
16	5/8	600	10,000	9.80	● C1130-20-00600	● C1134-20-00600	

12-Strand Braided Nylon



COMMERCIAL

DA-PRO

Da-Pro has a 12-strand construction with each strand utilizing lightweight polyolefin fiber sheathed in high tenacity polyester fibers. This unique construction produces a strong, lightweight rope that is firm/round, torque-free, and has excellent abrasion and snag resistance. Da-Pro is ideally suited for lifting and handline applications.

Ø mm	Ø in	Length ft	BL Lbs.	Weight lbs/100	Color/Item no. silver	Designed and best used as:
6	1/4	600	2,500	1.70	● C1300-08-00600	lifting, handline
8	5/16	600	4,150	2.50	● C1300-10-00600	
10	3/8	600	5,060	3.10	● C1300-12-00600	
11	7/16	600	6,350	4.30	● C1300-14-00600	
12	1/2	600	8,300	5.90	● C1300-16-00600	
14	9/16	600	10,400	7.50	● C1300-18-00600	
16	5/8	600	12,080	9.00	● C1300-20-00600	
18	3/4	600	16,500	12.20	● C1300-24-00600	
22	7/8	600	17,400	17.50	● C1300-28-00600	
24	1	600	19,425	24.50	● C1300-32-00600	

12-Strand Braided Polyolefin




COMMERCIAL

T-12

T-12 is a 12-strand single braid that is comprised of 100% Technora® and is characterized by very high tensile strength, very low stretch, zero creep, and excellent resistance to heat. T-12 comes standard with a black urethane coating

Ø mm	Ø in	Length ft	BL Lbs.	Weight lbs/100	Color/Item no. silver	Designed and best used as:
3	1/8	600	2,800	0.59	● C1564-04-00600	lifting, handline
5	3/16	600	5,300	1.19	● C1564-06-00600	
6	1/4	600	8,600	2.10	● C1564-08-00600	
8	5/16	600	12,000	3.10	● C1564-10-00600	
9	3/8	600	16,200	4.30	● C1564-12-00600	
12	1/2	600	33,600	8.00	● C1564-16-00600	

Urethane Coated Single Braid Technore®



COMMERCIAL

V-12

V-12 is treated with a proprietary urethane coating for improved abrasion resistance. This 12-strand single braid provides highest strength, lowest stretch and creep of any other 12-strand.



Ø mm	Ø in	Length ft	BL Lbs.	Weight lbs/100	Color/Item no. clear	red	green	blue	Designed and best used as:
3	1/8	600	2,100	0.46	● C1460-03-00600	● C1461-03-00600	● C1462-03-00600	● C1463-03-00600	lifting, handline
4	5/32	600	3,300	0.80	● C1460-04-00600	● C1461-04-00600	● C1462-04-00600	● C1463-04-00600	
5	3/16	600	4,950	1.20	● C1460-05-00600	● C1461-05-00600	● C1462-05-00600	● C1463-05-00600	
6	1/4	600	7,200	1.50	● C1460-06-00600	● C1461-06-00600	● C1462-06-00600	● C1463-06-00600	
8	5/16	600	10,900	3.30	● C1460-08-00600	● C1461-08-00600	● C1462-08-00600	● C1463-08-00600	
10	3/8	600	17,000	4.70	● C1460-10-00600	● C1461-10-00600	● C1462-10-00600	● C1463-10-00600	
11	7/16	600	26,000	6.60	● C1460-11-00600	● C1461-11-00600	● C1462-11-00600	● C1463-11-00600	
12	1/2	600	29,200	7.50	● C1460-12-00600	● C1461-12-00600	● C1462-12-00600	● C1463-12-00600	

Urethane Coated Single Braid Vectran®

New England Ropes® is part of Teufelberger Group.®



NEW ENGLAND ROPES

//////////////////////// est. 1967

Teufelberger Fiber Rope Corp.
848 Airport Road, 02720 Fall River, MA, USA

www.neropes.com

Official Line Provider of

